

MACKINAC COUNTY REMONUMENTATION CORNER

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac
(County)

Located In:

Corner Code ##

1. Public Land Survey

T 40N R 04W

P.C.C. 10

NW Cor. PC 10

2. Property Controlling
in Section

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY REGISTRAR OF DEEDS

DEC 11 1995

AM 7/8/9 PM 10/11/12/13/14/15/16

Register of Deeds Stamp & File Number

I, Neil E. Hill, in a field survey on NOVEMBER 17, 19 95,

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO notes. Set post.

12" Cedar N30E 15 lks.

6" Cedar S83E 25 lks.

See sketch on reverse of P.C.C. 8

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner prorated in relation to found fence corner in Sept. 1974 survey by Charlevoix Engineering & Abstract. Disregarded this location due to the final proration of entire line.

GLO for PC 9 & 10 693.0'

Charlevoix location 684.23' due to fence occupation.

Final location 692.69' total line proration.

Placed this corner at prorated distance on West Claim Line.

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1980 AT A MEETING
HELD ON 9-18-95
James H. Granger



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found nothing. Placed 5/8" re-rod std. county remonumentation corner.

10" Spruce N50W 36.95'

"T" Iron S50E 17.28'

6" Birch N50E 9.08'

Bent Pipe S50E 9.59'

4" Balsam S85E 22.65'

S50-18-03E 296.87 feet to SW Cor. PC 10

2" Cedar S70E 12.93'

N50-18-03W 366.13 feet to NW Cor. PC 11

Signed by Neil E. Hill P.S.

Date

NOVEMBER 17, 1995

Surveyor's Michigan License No. 27447