

# MACKINAC COUNTY REMONUMENTATION CORNER

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Mackinac  
(County)

Located In:

Corner Code ##

1. Public Land Survey

40N 4W

P.C.C. 1-4/1-5

T      R     

Section Corner

T      R     

common to

T      R     

Sec's 10 & 11 and

2. Property Controlling  
in Section

S      T      R     

North line of PC 19

S      T      R     

3. Miscellaneous  
Property in Sec.

S      T      R     

4. Lot No.                 , Recorded Plat                 

5. Private Claims                 

I, Neil E. Hill, in a field survey on SEPTEMBER 30, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G.L.O. notes. South between sec.'s 10 & 11, 74 ch.

Intersected North line of P.C. 19

10" Cedar S30E 17 lks

12" W. Pine N40W 20 lks

Found no evidence of corner.

Found evidence of survey by CA&E in N1/3 P.C. 19 for "Kidder".

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Set at GLO location from the NW corner of Private Claim #19 26 ch (1716.00 feet) between the NW corner of PC 19 and the intersection of the N-S Section line between Section 10 and Section 11 and the North Claim Line.

ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER P.A.  
345 OF 1990 AT A MEETING  
HELD ON 9-30-96

*James H. Branger*

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" rerod with 4" aluminum cap.

"T" iron N70W 1.75'

6" Tamarack N25E 7.74'

5" Cedar N85E 13.37'

8" Cedar S15E 6.41'

8" Cedar S65W 9.85'



Signed by Neil E. Hill P.S. P.C.

Date SEPTEMBER 30, 1996

Surveyor's Michigan License No. 27447