SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

Mackinac County Remonumentation Corner

For corners in


Mackinac County Located in: Corner Code # 1. Public Land Survey T42N R01W WCMC H/I-11 Ţ R Ţ R #005 R T Τ R 2. Property Controlling in Section R S T 3. Miscellaneous S R Т S Property in Sec.

RECEIVED & FILED DIANE FRANKOVICH MACKINAC COUNTY REGISTED OF DEEDS

FEB 2 5 2000

AM FIA 7[8]9[10]11[12]1[2]3[4[5]6

Register of Deeds Stamp & File Number



ACCEPTED BY THE MACKINAC COUNTY

11-05-90

of Mic

NEIL E

1413.1 Land

Surveyor

No.

27447

DLAHD

SURVEY PEER GROUP AS THE

OFFICIAL CORNER UNDER PA.

345 OF 1990 AT A MEETING

HELD ON

4 Lot No

, Recorded Plat

5. Private Claims

I, Neil E. Hill, in a field survey on 12-20-99, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845 GLO Notes J Mullett

10" Cedar for meander post

1953 C E Smith

Recorded the "Roach Plat", shows corner location, *No witnesses listed

1965 T L Jackson

Was ordered by a

Circuit Court Decree File No 1949 dated Nov 1961

Recorded Liber 173 Page 439, to reset the MC corner to the West

Book 1 Page 314

1981 Sherman Chamerlain - Charleviox A & E.

Fd Square rod

Shows location of corner on survey for Jack Law

*No witnesses listed

No Subsequent Information

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999 Fd Square rod in edge of lake marsh

Distance checks reasonably well to 1/4 Corner to the West

Set ½ rod with 4" Alum. remonumentation cap

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 1/2" rod with 4" Alum. remonumentation cap Corner is in marsh area at edge of lake, approx 25' from woods line

6" Ash N 30 E 13.55 2" Cedar S 25 W 32.54 6" Poplar S 55 W 14.91 8" Ash N 80 W 19.61

Bearings are compass bearings, corrected for declination, all distances are to a double- head nail in the side of the witness object unless otherwise noted.

Neil E. Shell ls, P.C. January 21 2000

Date

Surveyor's Michigan License No. 27447