

**MAR 20 2000**

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

**Mackinac County Remonumentation Corner**

For corners in

Mackinac County Located in: Corner Code #

1. Public Land Survey T42N R01W WCMC I-10/11  
T R  
T R  
T R  
#006

2. Property Controlling S T R  
in Section S T R

3. Miscellaneous S T R  
Property in Sec. S T R

4. Lot No. , Recorded Plat

5. Private Claims

**RECEIVED & FILED**  
**DIANE FRANKOVICH**  
MACKINAC COUNTY REGISTER OF DEEDS

**FEB 25 2000**

AM PM  
2181911011112111213141516

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, Neil E. Hill, in a field survey on 12-20-99, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845 GLO Notes A Burt 12" Aspen N 20 E 24 lks

No Subsequent Information

**ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER PA  
345 OF 1990 AT A MEETING  
HELD ON 1-05-00**  
*Neil E. Hill*

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1999 Fd 3/4" Pipe, is on an extension line from Section corner and 1/4 corner to the North.  
Accepted corner location  
Placed 4" Alum. remonumentation cap

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner is a 3/4" Pipe with 4" Alum. remonumentation cap

6" Ash N 30 E 11.60'  
3" Ash N 50 E 8.38'  
4" Ash S 55 E 6.84'  
6" Ash S 40 W 11.89'



Bearings are compass bearings, corrected for declination, all distances are to a double-headed nail in the side of the witness object unless otherwise noted.

Signed by *Neil E. Hill P.S., P.C.*

Date January 21 2000

Surveyor's Michigan License No. 27447