

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

Mackinac Co.

3 Corners.

| FOR CORNERS OF-- | LOCATED IN-- | CORNER CODE NUMBER |
|---|--------------|-----------------------|
| 1. PUBLIC LAND SURVEY_____ T. _____ N. _____ E. _____ S. _____ R. _____ W. _____ | | |
| 2. PROPERTY CONTROLLING IN SECTION <u>3</u> , T. <u>42</u> N. <u>8</u> , R. <u>7</u> E. <u>1</u> W. _____ | | <u>4</u> |
| 3. MISCELLANEOUS PROPERTY IN SECTION <u>3</u> , T. <u>42</u> N. <u>8</u> , R. <u>7</u> E. <u>1</u> W. _____ | | <u>4-8 & G2-3</u> |
| 4. LOT NO. _____ , RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David Babbitt, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 11-30, 1981, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on 11-30, 1981, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
Corners not previously established.

-8 1/64 Corner in NW 1/4.

North-West 1/16 Corner of Section 3.

2-3 1/64 Corner on West Section Line Section 3.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

-8 Set Mid Point on Line between 1/16 Corners, code 4 and 8.

Set at the computed center of the N.W. 1/4 of Section 3 by closed traverse.

2-3 Set Mid Point on Line between the W1/4 Corner of Section 3 and the N1/16 Corner on the West Section Line of Section 3.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
at D.N.R. monument at all three corners. bearings:

-8 6" Beech, S45°W, 7.4' & 6" R. Maple, N85°W, 11.45'
6" Beech, N15°W, 17.4' & 12" Beech, S86°E, 13.0'

18" Beech, N7°E, 28.7' & 6" W. Pine, S63°E, 5.3'
8" R. Maple, S28°E, 48.1' & 10" R. Maple, N72°W, 56.9'

2-3 7" R. Maple, N69°W, 63.3' & 14" R. Maple Clump, N6°W, 55.45'

SIGNED BY David A. Babbitt DATE 12-21-81

David Babbitt

SURVEYOR'S MICHIGAN REGISTRATION NO. 21558

(SEAL)

FOR STATE AND UNITED STATES AGENCIES: