

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Mackinac
(County) Located In: Corner Code #

1. Public Land Survey	T 42N R 4W	H-11
	T R	
	T R	
	T R	
2. Property Controlling	S T R	
in Section	S T R	
3. Miscellaneous	S T R	
Property in Section	S T R	

4. Lot No. , Recorded Plat

5. Private Claims

RECEIVED & FILED
DIANE FRANKOVICH
MACKINAC COUNTY REGISTER OF DEEDS

OCT 29 1996
AM PM
7|8|9|10|11|12|1|2|3|4|5|6

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, David B. Guthrie in a field survey on October 9, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1845: G.L.O. Survey by J.A. Mullett - Cedar 10 in. for 1/4 Section Corner

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1996: Found no evidence of corner. Set a 5/8" Iron Rod by East West proportionate measurement between the North 1/4 Corner of Section 33 and the Northeast Corner of Section 35, in the center of Charles Moran Road.

SURVEY &
REMONUMENTATION

MAY 20 1997

COMMISSION

ACCEPTED BY THE MACKINAC COUNTY
SURVEY PEER GROUP AS THE
OFFICIAL CORNER UNDER P.A.
345 OF 1990 AT A MEETING
HELD ON 8-26-96

James H. Dranger

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1996: Set a 5/8" x 24" Iron Rod with an Aluminum Cap stamped to identify the corner.

Referenced: S41°W - 10" Spruce - 48.87 feet
S40°E - 4" Spruce - 53.81 feet
N18°E - 7" Birch - 52.40 feet
N65°E - 8" Birch - 72.62 feet



Signed by David B. Guthrie Date Oct. 10, 1996

Surveyor's Michigan License No. 22435