

**JAN 21 1999**

**SECTION**

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**  
**Mackinac County Remonumentation Corner**

For corners in

Mackinac County

Located in:

Corner Code #

1. Public Land Survey

T43N R1W  
T43N R1E

M-6  
A-6 (Same corner  
Chippewa County)

2. Property Controlling  
in Section

S

T R  
T R  
T R

3. Miscellaneous  
Property in Sec.

S

T R  
T R

4. Lot No.

, Recorded Plat

5. Private Claims

ACCEPTED BY THE MACKINAC COUNTY  
SURVEY PEER GROUP AS THE  
OFFICIAL CORNER UNDER P.A.  
345 OF 1990 AT A MEETING  
HELD ON 11-20-98 NEH

**RECEIVED & FILED**  
**DIANE FRANKOVICH**  
MACKINAC COUNTY REGISTER OF DEEDS

**DEC 30 1998**

AM

PM

7|8|9|10|11|12|1|2|3|4|5|6

Register of Deeds Stamp & File Number

I, Keith R. Waters, in a field survey on November 11, 1998, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey Instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-6 1/4 Corner Common to Section 13, T43N, R1W & Section 18, T43N, R1E

1840 - Original corner established by William A. Burt.

1991 - Neil E. Hill, P.S. 27447, set 1/4 corner on line between section corners 2641.74' north and 2629.74' south, at a fence line to the west and a brushed line to the east. Preserved corner prior to road construction.

1992 - LCRC, liber 7, page 357, Chippewa County corner records. Neil E. Hill, P.S. 27447, reestablished corner after road construction from 1991 witnesses. Set a 1/2" iron with cap #27447 in a monument box. Witnesses:

Nail and MDOT tag in power pole, N70°W 72.82'

Nail and MDOT tag in corner fence post, WEST 75.67'

Nail and MDOT tag in southerly gate post, S65°W 106.43'

Top center of right-of-way marker, EAST 75.64'

Nail and MDOT tag in 8" tamarack, S75°E 133.46'

Section corners, NORTH 2641.74' and SOUTH 2629.74'

1994 - LCRC, liber 8, page 315, Chippewa County corner records. Keith R. Waters, P.S. 33142, found a 1/2" iron with cap #27447 in a monument box and all record witnesses from 1992 LCRC.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

This corner is being perpetuated as part of the Mackinac County Remonumentation Program.

Found a 1/2" iron with cap #27447 in a monument box. Also found all record witness objects as called for in the 1992 and 1994 LCRC's, except for the 8" tamarack.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Found a 1/2" with cap #27447 in a monument box at the corner location, which falls in Highway M-129. Witnesses:

Nail and MDOT tag in power pole (E35), N70°W 72.82'

Nail and MDOT tag in corner fence post, WEST 75.67'

Nail and MDOT tag in southerly gate post, S65°W 106.43'

Top center of concrete right-of-way marker, EAST 75.64'

"+" in top of headwall, S64°E 32.22'

1" iron pin in monument box at section corner (M-5), NORTH 2641.74'

1" iron pin in monument box at section corner (M-7), SOUTH 2629.74'

Signed by

Keith R. Waters

Date

12-23-98

Surveyor's Michigan License No. 33142

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
REVISED OCT., 1995

T43N R1W M-6

**E - 247**

