

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Mackinac (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 15 T 43N R 10W	7
	S 15 T 43N R 10W	6
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 10/20/2010 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(7-Sec. 15) North 1/16 corner between Sections 14 and 15. Not established in the original survey.

(6-Sec. 15) Northeast 1/16 corner, Section 15. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(7-Sec. 15) Established the corner midway and on the Section line between Section corner 1315.40' north and Quarter corner 1315.40' south.

(6-Sec. 15) Established the corner at the intersection of straight lines connecting opposite 1/16 corners. From the position for the corner the physical centerline of Co.Rd. H40, which bears NE-SW, is S20E 20.7'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(7) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
25" W.Pine S24E 13.5' mrkd "N1/16 BT"
6" B.Spruce S88E 19.45' do
7" Maple N69W 11.4' do
11" Maple N52E 31.8' do
Bearings are magnetic.

(6) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
7" Black Ash N49W 63.25' mrkd "NE1/16 BT"
6" W.Birch S09W 94.22' do
8" W.Birch S23W 108.90' do
Power pole S32E 58.07'
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 11/15/2010

For the Michigan Department of Natural Resources and Environment, Forest Management Division



47411

47412