

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Mackinac

(County)

Located In:

Corner Code #

1. Public Land Survey

T 44N R 7W

A12

T R

T R

S

T R

2. Property Controlling  
in Section

S 31

T 44N R 7W

11

S T R

3. Miscellaneous

S

T R

Property in Sec.

S

T R

Register of Deeds Stamp & File  
Number

4. Lot No. , Recorded Plat

5. Private Claims

11 Jun 08 2005

A12 Nov 02 2005

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(A12) Quarter corner on the west side of Section 31 T44N-R07W. Not established in the original survey. Found no subsequent record.  
(11-Sec. 31) Southwest 1/16 corner, Section 31. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A12) Established the corner midway between Section corner A13 and Closing corner A11 and on line between Standard corners M12 and M11 of T44N-R08W. The position for the corner falls 26.49' north of the Standard Quarter corner M12 T44N-R08W.  
(11-Sec. 31) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A12) Set 1"IDx36" I.pipe with 4" alum.  
MDNR cap. Set measuring nails in:  
10" Cedar S30W 3.35' mrkd "1/4S NBT"  
6" Cedar N59E 6.05' do  
8" W.Birch N06E 15.4' do  
12" Cedar N80W 18.97' do  
DNR monument at M12 T44N-R08W S04W  
26.49'. Bearings are magnetic.  
Distances are to nail with tag.

(11) Set 5/8"x18" rebar w/plastic cap  
marked MICH DNR PS 33986 set flush with  
road surface. Set measuring nails in:  
Power pole E-26 S09E 41.95'  
Sign post N66W 38.53'  
6" Elm N28E 26.05' mrkd "SW1/16 BT"  
15" Maple S37E 99.5' do  
Center of pavement of Hiamatha Trail,  
South 11.0'. Bearings are magnetic.  
Distances are to nail with tag.



Signed by

*Stephan J. Szyszkoski*

Date

1/26/06

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Office of Land and Facilities