

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

Mackinac Co.

2 Corners.

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. <u>44</u> N. R. <u>10</u> W.	<u>C-2</u>
2. PROPERTY CONTROLLING IN SECTION <u>5</u>	T. <u>44</u> N. R. <u>10</u> W.	<u>3-Sec. 5</u>
3. MISCELLANEOUS PROPERTY IN SECTION	T. N. R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Billy D. Buckler, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 6-12, 19 78, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

C-2 Quarter Corner between Sec's. 5-6, set by Wm Ives, D.S. in 1849.
Bearings were: Beech 6, S20°W, 18 lks. and Sugar 17, N40°E, 10 lks.

3-Sec. 5 North 1/16 Corner on Westside of Section 5.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-2 Corner restored by Single Proportionate Measure between two Section Corners.

3-Sec. 5 Corner placed by single proportionate measure between Section Corner to North and $\frac{1}{4}$ Corner to South.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Placed 1" pipe with 4" aluminium cap at both corners.

C-2 New Bearings: 6" Maple, S74°E, 1.4' and 8" Maple, S16°W, 15.6' and
6" Maple, N76°W, 31.6'.

3-Sec. 5 Bearings: 6" Maple, N18°E, 5.1' and 18" Maple, N82°W, 36.2' and
14" Maple, S47°W, 38.0'.

SIGNED BY

Billy D. Buckler

DATE 9-11-78

SURVEYOR'S MICHIGAN REGISTRATION NO. 8887

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY

CHIEF OF SURVEY PARTY

DATE

APPROVED AND SIGNED BY

MICHIGAN REGISTERED LAND SURVEYOR

DATE

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

