## LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970 Mackinac Co.

FOR CORNERS OF-:	LOCATED IN-:	CORNER CODE NUMBER	
1. PUBLIC LAND SURVEY	T. 11 N. R. 11 W.	E-6	·
2. PROPERTY CONTROLL-	N. E. T S. R W.		
	,		
PROPERTY IN SECTION.	,T		1
4. LOT NO , REC	CORDED PLAT		,
5. PRIVATE CLAIMS			
J. PRIVATE CEMAS			REGISTER OF DEEDS STAMP AND
the corner points mentioned field survey on	in lines 1 and 2 above (iden 6/161972, established and in conformance with regu United States Department of e, that the corner points me, found, recovered, restored, e	tified with circles on inder I, re-established, monument lations and rules therefore of the Interior, Bureau of Land entioned in lines 3,4 and 5 stablished or re-established	P.A. 74, Michigan P.A. of 1970, a code diagram—over) were, in a sed, re-monumented, recovered or as required in the current manual Management or by a decree of a above were, in a field survey on a sexpressed below and in contess or, by a Decree of a Court of
-	nument and accessories and/laced by William Ives	=	
Bearings were:	5" \$16°E 20 Links	*	
LEDATO	9" N20°W 43 Links	and the second s	•
Beech			
Beech		•	
Beech			
B. Description of corner evid  Found a lin iron at corner in place pri	ence found and/or method ap corner, placed by unl	known Surveyor. Land	
B. Description of corner evid Found a lin iron at corner in place pri	ence found and/or method ap corner, placed by unl or to 1958.	known Surveyor. Land	
B. Description of corner evid Found a lin iron at corner in place pri	ence found and/or method ap corner, placed by unl or to 1958.	known Surveyor. Land	
B. Description of corner evid Found a lin iron at corner in place pri	ence found and/or method ap corner, placed by unl or to 1958.	known Surveyor. Land	
B. Description of corner evid Found a 1½" iron at corner in place pri Corner lies 144° So  C. Description of monument Placed a 1" pipe wi	ence found and/or method ap corner, placed by unl or to 1958. uth of an old Grade.	established to perpetuate loc	
Beech  B. Description of corner evid  Found a l½n iron at corner in place pri Corner lies 1441 So  C. Description of monument Placed a ln pipe wi New Bearings: 9" Sof	ence found and/or method ap corner, placed by unl or to 1958. uth of an old Grade.	established to perpetuate loc	owners repert this
Beech  B. Description of corner evid  Found a l½n iron at corner in place pri Corner lies 1441 So  C. Description of monument Placed a ln pipe wi New Bearings: 9" Sof	ence found and/or method ap corner, placed by unl or to 1958. uth of an old Grade. for corner and accessories e th 4" aluminum cap at	established to perpetuate loc	owners repert this
Beech  B. Description of corner evid  Found a l <sup>1</sup> / <sub>2</sub> " iron at  corner in place pri  Corner lies 144° So  C. Description of monument  Placed a l" pipe wi  New Bearings:  9" Sof	ence found and/or method ap corner, placed by unl or to 1958. uth of an old Grade. for corner and accessories e th 4" aluminum cap at	established to perpetuate loc	owners repert this
B. Description of corner evid Found a 1½" iron at corner in place pri Corner lies 1441 So  C. Description of monument Placed a 1" pipe wi New Bearings: 9" Sof	for corner and accessories eth 4" aluminum cap at thaple \$28°W 41.7'	established to perpetuate loc corner.	owners repert this
B. Description of corner evid Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings:  9" Sof 14" Har	for corner and accessories eth 4" aluminum cap at t Maple S28" 41.7"	established to perpetuate loc corner.	eating the position of the corner:
Beech  B. Description of corner evid  Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings: 9" Sof 14" Har	ence found and/or method ap corner, placed by unlor to 1958. The corner and accessories of the saluminum cap at th	established to perpetuate locations.	eating the position of the corner:
B. Description of corner evid Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings:  9" Sof 14" Har	ence found and/or method ap corner, placed by unlor to 1958. The corner and accessories of the saluminum cap at th	established to perpetuate locations.	eating the position of the corner:
Beech  B. Description of corner evid  Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings:  9" Sof 14" Har	for corner and accessories eth 4" aluminum cap at t Maple N68°W 19.3°d Maple S28°W 41.7°d	established to perpetuate locations.	cating the position of the corner:
Beech  B. Description of corner evid  Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings:  9" Sof 14" Har	for corner and accessories eth 4" aluminum cap at t Maple N68°W 19.3" d Maple S28°W 41.7"  CGISTRATION NO.	established to perpetuate local corner.  DATE 6	cating the position of the corner:
Beech  B. Description of corner evid  Found a 1½ iron at corner in place pri Corner lies 144 So  C. Description of monument Placed a 1" pipe wi New Bearings:  9" Sof 14" Har	for corner and accessories of the saluminum cap at thaple N68°W 19.31 d Maple S28°W 41.71  College of Survey Party	Stablished to perpetuate local corner.  DATE  DATE	cating the position of the corner:

Form No. ML M736 DOMESSAY BROS. B. CO., KALAMAZOO, MICH. FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971 DISTRIBUTED BY MICHIGAN SOCIETY OF REGISTERED LAND SURVEYORS