

SURVEY &
REMONUMENTATION

APR 28 1995

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

C152236

94 DEC 14 AM 10:53

For corners of **COMMISSION**
MACOMB
(County)

Located In: **Sterling**
Township Corner Code **##**

CAL. REGIS. DEEDS
MACOMB COUNTY, MI

1. Public Land Survey T 2N R 12E A-1
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S _____ T _____ R _____
in Section S _____ T _____ R _____
3. Miscellaneous S _____ T _____ R _____
Property in Sec. S _____ T _____ R _____

LIBER **6527** PAGE **813**

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	13	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

I, **Randy Kolehose**, in a field survey on **June 23**, 19 **94**,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

A-1	1817	G.L.O.	Notes	Wampler	NA	Post
	1928	MCRC	File #169	NA	NA	Ford Axle in M.B.
	1972	Survey	L. 2271 P. 2	Patterson	#17631	NA
	1974	Survey	L. 2466 P. 726	Kobs	#14097	Iron in M.B.
	1974	L.C.R.C.	L. 2466 P. 738	Kobs	#14097	1/2" Iron in M.B.
	1986	L.C.R.C.	L. 4089 P. 888	Avey	#30076	Boat Spike in M.B.
	1989	L.C.R.C.	L. 04665 P. 607	Patterson	#17631	Boat Spike in M.B.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- A-1 Found 5/8" rebar with brass cap marked (Oakland Co. Remon. #17632) in Monument Box at center line in
Intersection of Dequindre and South Blvd.

L.C.R.C. L. 2466 P. 738
PK in D.E. Pole SW 84.2'

L.C.R.C. L. 4089 P. 888
PK/W in Utl. Pole SW 84.2'
Nail in Utl. Pole SE 88.4'
Nail in Utl. Pole NE 86.63'
Nail in Utl. Pole NW 85.99'

L.C.R.C. L. 04665 P. 607
Nail in Utl. Pole NE 86.63'
Nail in Utl. Pole SE 88.40
Nail in Utl. Pole SW 84.20'

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990 AT A MEETING HELD
ON **9-20-94**

William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

Measure E 2644.56 to B-13 (G.L.O. 2645.28)
This corner is common with A-13 T3N R12E

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

- A-1 5/8" rebar with Brass Cap stamped "Oakland Co. Remon #17632 in an existing monument box.

PK & Oakland Co. Remon. Tag in NE Face Utl. Pole N 38° W 85.96'
PK & Oakland Co. Remon. Tag in NE Face Utl. Pole S 40° E 88.39'
PK & Oakland Co. Remon. Tag in SE Face Utl. Pole N 36° E 86.63'
PK & Oakland Co. Remon. Tag in Nly Face Utl. Pole S 50° W 83.70'

The selected location is accepted by me and is generally accepted by professional surveyors as the best
available evidence of the position of the original corner.

Signed by *Randy J. Kolehose*
Surveyor's Michigan License No. **25854**

Date **10/14/94**

