

SURVEY & REMONUMENTATION

APR 28 1995

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

C152246

or corners in

MACOMB

(County)

Located In: Sterling Township Corner Code #

Public Land Survey	T 2N R 12E	E-6
	T R	
	T R	
	T R	
	T R	
Property Controlling in Section	S T R	
	S T R	
Miscellaneous	S T R	
Property in Sec.	S T R	

94 DEC 14 AM 10:53

3/4" IRON
RECORDED
MICOMB COUNTY, MI

LIBER 6527 PAGE 823

Register of Deeds Stamp & File Number

Lot No. , Recorded Plat
Private Claims

Randy Kolehouse in a field survey on July 25, 1994

o hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

OTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

E-6	1817	G.L.O.	Notes	Wampler	N/A	Post
	1992	MCRC	File #70	Campbell	N/A	1/2" Iron

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5		4	3	2	1						
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

E-6 Found 1/2" Iron in center line median Mound Road on line of tree row running west and on line of fence running east, checks 102.0 feet East to plat corner monument at SE corner, Lot 34, Mound Grove Gardens Subdivision. Liber 19 Page 48 MCR

Checks the following MCRC Wit.
PK in Face of M.B.T. Pole ENE 107.0'
PK in Face of D.E. Pole W 93.89'

Measure N 2654.56 to E-5 (MDOT 2655.42) (G.L.O. 2640)
Measure S 2621.59 to E-7 (G.L.O. 2640)

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 9-20-94
William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

E-6 I replaced the found 1/2" Iron with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County Monument MI Act 345 #25854."

Nail and MSHD Tag in N Face Util. Pole N 86° W 93.89'
PK in S Face Util. Pole 106.95'
Conc. Plat Monument E 101.9'
"+" on N Rim M.H. S 16° E 24.82'
PK and MCRC Tag in E Face Util. Pole S 47° W 141.54'

The selected location is accepted by me and is generally accepted by professional surveyors as the best available evidence of the position of the original corner.

igned by *Randy J. Kolehouse*
Surveyor's Michigan License No. 25854

Date 10/12/94

