

SURVEY &
REMONUMENTATION

APR 28 1995

C152211

COMMISSION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MACOMB

(County)

Located In: Clinton
Township

Corner Code --

LIBER 6527 PAGE 788

1. Public Land Survey T 2N R 13E A-8
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

94 DEC 14 AM 10:51
REGISTERED
Register of Deeds Stamp & File Number
CLINTON TOWNSHIP, MI

4. Lot No. , Recorded Plat
5. Private Claims

I, Randy Kolehhouse, in a field survey on June 30, 19 94,
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned
in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the Interior, Bureau of Land
Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5
above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a
Court of Law; established, re-established, monumented, re-monumented, recovered, found as
expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded
on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

A-8	1817	G.L.O.	Notes	Wampler	N/A	Post
	1934	MCRC	Field Notes	N/A	N/A	"+" in Pavement
	1984	MCRC	Field Notes	N/A	N/A	PK Nail
	1991	L.C.R.C.	L. 5509 P. 445	Patterson	#17631	PK Nail

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

A-8 Found PK Nail in Center Line of Hayes Road over a 1" iron pipe which is 6" below asphalt road surface in old
concrete roadway.

MCRC Field Notes (1984)
PK in NE Face Util. Pole ESE 52.32'
Center Line Hyd. SE 66.05'
PK in SE Face Util. Pole SW 80.10'

L.C.R.C. L. 5509 P. 445
PK in 18" Ash E 100.87'
PK in Util. Pole S 45° W 80.14'
PK in Util. Pole N 30° W 66.88'

Measure N. 2701.00 to A-7 (River Park Estates = 2700.3) (G.L.O. 2640)
Measure S 2641.87 to M-9 (G.L.O. 2640)
This corner location is common with M-8 T2N R12E.

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990 AT A MEETING HELD
ON 9-20-94
William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

A-8 I replaced the found PK Nail with a 3/4" x 24" Iron Rod w/2" diameter aluminum cap stamped "Macomb County
Monument MI Act 345 #25854," set Monument Box.

PK with Tag "GW #78155" S Face 24" Ash S 82° E 100.76'
PK NE Face Util. Pole S 38° E 52.27'
Center Line Top Nut Fire Hyd. S 37° E 65.90'
PK E. Face Util. Pole S 30° W 80.04'
Nail with Tag "GW #78154" SW Face Util. Pole N 28° W 61.83'

The selected location is accepted by me and is generally accepted by professional surveyors as the best
available evidence of the position of the original corner.

Signed by Randy J. Kolehhouse
Surveyor's Michigan License No. 25854

Date 10/14/94

