

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Macomb (County)	Located In: Shalby Twp.	Corner Code #
1. Public Land Survey	T 3N. R 12E.	C-7
	T R	
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	

SURVEY &
REMONUMENTATION

MAR 15 1999

SECTION

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER
GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN
PUBLIC ACT 345 OF 1990 AT A MEETING HELD
ON 10/19/98

William E. Soderberg
WILLIAM E. SODERBERG, P.S., CHAIRMAN

I, Jeffrey A. Wright, in a field survey on 24 August, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

Date	Surveyor	Number	Type	L.	P.	Monument Box
1817	Wampler		Set Post			No
1976	Kobs	14097	F. 1/2" bar Act 132	GLO Records	864	Yes
1976	Kobs	14097	F. 1/2" bar Act 74	2723	879	Yes
1989	Avey	15396	F. 1/2" bar Act 132	Unrecorded		Yes
1990	Avey	15396	F. 1/2" bar Act 74	4983	759	Yes
1990	Avey	15396	F. 1/2" bar Act 132	Unrecorded		Yes
1996	Marini	26462	F. 1/2" bar Act 74	7168	88	Yes

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found 1/2" bar in monument box, as previously recorded.

(Located at the int. of 23 Mile Rd. & Ryan Rd.)

Location supported by corners in:

Kemler Sub. L. 41, P. 32
Kemler Sub. #1 L. 42, P. 20
Kemler Sub. #2 L. 44, P. 45
Spring Lake Sub. L. 123, P. 30-34
Spring Lake Sub. #2 L. 77, P. 11-14

Ground Distances:

C-7 to D-7 = 2744.87' m.

GLO: C-7 to D-7 = 80.10 ch. (2643.30')

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3/4" bar with an aluminum cap stamped "Macomb County Monument - MI Act 345 #40165"
in an existing monument box.

52.00' (AZ. 5°) to MAG nail w/ Macomb County Witness Tag in W side U. pole
167.09' (AZ. 292°) to MAG nail w/ Macomb County Witness Tag in SW side U. pole
84.10' (AZ. 252°) to MAG nail w/ Macomb County Witness Tag in NW side U. pole
60.18' (AZ. 218°) to MAG nail w/ Macomb County Witness Tag in SE side U. pole
56.66' (AZ. 137°) to MAG nail w/ Macomb County Witness Tag in SW side U. pole



The selected location is accepted by me and is generally accepted by Professional Surveyors as the best available evidence of the position of the original corner.

Signed by

Jeffrey A. Wright

Date:

12 NOVEMBER 1998

Surveyor's Michigan License No. 40165