

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MACOMB

(County)

SHELBY TOWNSHIP

Located In:

Corner Code #

1. Public Land Survey

T 3N R 12E

M3

2. Property Controlling  
in Section

S

T

R

S

T

R

3. Miscellaneous  
Property in Sec.

S

T

R

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

I, CRAIG P. AMEY, in a field survey on AUGUST 14, 1999, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

A. 1817 GLO J. WAMPLER  
B. 1979 LCRC, L. 3186 P. 877 H. KOBS #14097  
C. 1993 LCRC, L. 6166 P. 81 D. PAWLACZYK #17632  
D. 1995 LCRC, L. 6832 P. 280 J. WRIGHT #40165

SET POST  
FOUND 1/2" PIPE IN MONUMENT BOX  
SET 3/4" IRON WITH REMON. CAP IN MONUMENT BOX.  
FOUND REMONUMENTATION MARKER IN MONUMENT BOX

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4" IRON IN MONUMENT BOX 1.0' BELOW GRAVEL SURFACE IN THE CENTER OF HAYES ROAD

20° 154.34 FOUND PK WITH GWE TAG IN THE EAST FACE OF A UTILITY POLE (C. 154.27, D. 154.30)  
250° 88.68 FOUND PK WITH MACOMB COUNTY WITNESS TAG IN NORTHWEST SIDE OF A UTILITY POLE (C. 88.64, D. 88.63)

THE CORNER AGREES WITH WITNESSES IN THE LCRC APPROVED BY THE MACOMB COUNTY REMONUMENTATION PEER GROUP. ADDITIONAL WITNESSES WERE SET PRIOR TO THE RECONSTRUCTION OF HAYES ROAD. THE CORNER WAS RESET AND RE-WITNESSED AFTER THE CONSTRUCTION WAS COMPLETED.

DISTANCES TO ADJACENT REMON CORNERS

M3 - M2 2783.28 (GLO 40.00 CH, 2640.00') M3 - A3 (T3N,R13E) 157.32' (GLO 1.48LKS. 0.97')  
M3 - M4 2696.99 (GLO 40.00 CH, 2640.00') M3 - L3 2618.46 (GLO 39.73 CH, 2622.18')

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 3/4" IRON IN MONUMENT BOX WITH ALUMINUM MACOMB COUNTY REMONUMENTATION CAP #34970

20° 154.34' FOUND PK WITH GWE TAG IN THE EAST FACE OF A UTILITY POLE  
55° 43.91' FOUND PK IN THE SOUTHEAST FACE OF A UTILITY POLE  
250° 88.68' FOUND PK WITH MACOMB COUNTY WITNESS TAG IN THE NORTHWEST SIDE OF A UTILITY POLE  
340° 47.76' NORTH CORNER OF ROAD CATCH BASIN CASTING AT TOP/BACK OF CURB

THE SELECTED LOCATION IS ACCEPTED BY ME AND IS GENERALLY ACCEPTED BY PROFESSIONAL SURVEYORS AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER

Signed by

Date

12-28-99

Surveyor's Michigan License No. 34970

1166  
LIBER 9275 PAGE 517  
01/04/2000 09:29:18 A.M.  
MACOMB COUNTY, MI  
CARNELLA SABAUGH, REG/DEEDS

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

ACCEPTED BY THE MACOMB COUNTY SURVEY PEER GROUP AS THE OFFICIAL CORNER UNDER MICHIGAN PUBLIC ACT 345 OF 1990 AT A MEETING HELD ON 10/26/99

WILLIAM E. SCHUBERT, P.S., CHAIRMAN

