PENONUMENTATO

DEC 2 9 1998

SSION

LAND CORNER RECORDATION CERTIFICATE	COMMIS
 Filing Requirement of Act 74, Mich. P.A. 1970	

For corners in		1	F	FGIS	TED	פ טבנ						
Manistee (County)						REGISTER'S OFFICE MANISTEE COUNTY						
1. Public Land Survey	T_21N R 17W	M-05 W.C.		97-388 at 3:20pm OCT 17 1997								
22.10 24.10	T R	South of the		.) -	0 .							
	TR	Southeast Sec.	<u> </u>	TE DOTA		·		_				
D. Duning a street Control 181	<u>TR</u>	Corner of		REGIS	STER (OF DE	EDS					
2. Property Controlling in Section	S H	Section 12										
3. Miscellaneous	S R		_									
Property in Sec.	S T R	(#2)	Ke Nu	Register of Deeds Stamp & File Number								
4. Lot No, Rec 5. Private Claims	orded Plat		A R	c D	E F	g H	ı	,	т. м			
5. Tivate Claims			1		<u> </u>	11	- j -	[]	[]			
	•		2 - 6 -	5	'4	. 3	2-		1			
I, Anthony M. Slawinski	in a field survey on July ?	30 , 19 <u>97</u> do hereby state that	3	} 	·		}}					
under requirements of P.A. 74, I above were in conformance with	Michigan P.A. of 1970, the corner of the cor	r points mentioned in lines 1 and 2 as required in the current manual of	4	ģ	<u> </u>	10			2_			
survey instructions of the United	d States Department of the Interio	or, Bureau of Land Management or	5			 						
by a decree of a Court of Law	and for that the corner points me	entioned in lines 3, 4 and 5 above	618	1-17-	16	 15	14-		13-			
Court of Law: established, re-est	rules of the Michigan Board of La tablished, monumented, recovered	and Surveyors or by a Decree of a	7	 		<u> </u>		<u> </u>	1			
			B 1 g	20_	 2 1	22-	23-	2	2 4-			
	orners, all in the same town an	d range, may be recorded	9	1_1_		<u> </u>						
on this certificate.	•		10-30-	2 9	28		26-		2 5			
A. Description of original m	onument and accessories and/	Or subsequent restoration:	11									
M-05 Meander Corner South	of the South east Section Co	orner of Section 12, T21N., R17	W. 12-31-	32-	 33	34	3.5	<u>.</u>]	3 6-			
Set by John Brink in 1838		•	13	<u> </u>								
73,70 Chains Int. West Marg 1. Beech 11" S 51 ½° E 2. W. Ash 8" S 38 ½° W	The state of the s	t .						물 6	<u></u>			
B. Description of corner ev M-05 Meander Corner South	ridence found and/or method and of the South east Section Co	applied in restoring or reestablish orner of Section 12, T21N., R17	ing corner: W.					7 Ber Gre 15 of 190	MCL 54.2			
which is common to the Oak computed location of the Eas of Bob Griffin on July 18, 19	: Hill Plat and the First Rietz Pa st ¼ Post to establish the loca	g the North-South Range line and ark Addition Plat, and used gover ation of the Meander corner. This he Meander Corner in its compute position on line.	rnment mea s was done	sure fro	m the	1	ratified by the Manistee Count.	pursuant to P.A. 32	E minorisment Agn			
Also Referenced: GLO Original Field Notes, Brit	nk (1838) Book 1, pages 283-						d by th	ted pro	4			
Survey Map by Jenema (199	14)	Corner & the Meander by Abonmarche (1997		Witnes	s Corn	ers		C/S	OF.			
		tablished to perpetuate locating orner of Section 12, T21N., R17		of the	corner	":	. (State	Review			
from the calculated East ¼ corner. The calculated position to set the corner in this local	corner of Section 13, T21N., I on put the corner inside a build tion, I continued North on line	nt, flush to the ground, by measu R17W., North to the calculated plant ding at the Ambar chemical plant 425.80 feet and set a witness c ad by: The area were ori	position of t t. Then, bec corner as a c	he mea ause l areful	nder was ur and fal	nable thful	according to the com	amended, (being the	Jage of Page			
3. N 33° W 244.55′ Fenc		OF MICH					Accord	Se and				
4. S 44° W 184.83′ Fenc			0/				-4	O	•			
5. S 30° W 314.18′ Build6. S 03° E 130.68′ 4″ Mc		/5/ M.	121									
U. U UU E 13U.00 4 MI	AUCOL AACIL	SLAWINSKI	1-1									
Note: the corner lies ±20' So	outh of Manistee Lake	SURVEYOR NO.	/8									

Signed by Anthrony m.
Surveyor's Michigan License No. 13597