## SECTION

Surveyor's Michigan License No. 13597

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

| For corners in   | ,  | 1  | DECISTEDIO OFFICE   |
|--|--|--|---|
| Manistee (County)  | Located In:  | Corner Code #  | REGISTER'S OFFICE MANISTEE COUNTY 99-2200±1:10pm                                |
| 1. Public Land Survey  | T_21N R_17W_<br>T R<br>T R<br>T R  | L-03 MC East of South 1/4 Cor., Sec. 1   | JUL 22 1999<br>Deborah Six<br>REGISTER OF DEEDS                                 |
| 2. Property Controlling S_ in Section S_ 3. Miscellaneous S_ Property in Sec. S_ 4. Lot No, Record 5. Private Claims   | T R R T R R R R R R R R R R R R R R R R  | #008   | Register of Deeds Stamp & File<br>Number  |
| I, Anthony M. Slawinski, in under requirements of P.A. 74, Michabove were in conformance with resurvey instructions of the United Stoy a decree of a Court of Law and were in conformance with the rules Court of Law; established, re-established. Rote:  NOTE: Not more than 2 corne on this certificate.  A. Description of original mon L-O3MC Meander Corner East of Set by John Brink in 1839 3.13  1. B. Oak 8" dia. S 70° W 22. W. Oak 10" dia. N 57° E  | higan P.A. of 1970, the corner gulations and rules therefore a tates Department of the Interior that the corner points miss of the Michigan Board of Lished, monumented, recovere ers, all in the same town as ument and accessories and of South ¼ Corner, Section 3 chains east of South ¼ C22 links (14.52')  | or points mentioned in lines 1 and 2 as required in the current manual of lor, Bureau of Land Management or lentioned in lines 3, 4 and 5 above and Surveyors or by a Decree of a d, found as expressed below:  Ind range, may be recorded  If or subsequent restoration:  In 1, T21N, R17W  | 2 6 5 4 3 2 1   |
| C. Description of monument of L-03MC Meander Corner East  On June 7, 1999, I Anthony S line established to set the Sour from the South ¼ Corner of S to dispute the location of the compact of the position of the | of chain link fence measur corner of building #3 measure corner of building #2 measure corner of building #2 measure corner of building #2 measure corner, Section 1 % Corner of Section 1 % Corner of Section 1 % Corner of Section 1 % Corner.  For corner and accessories to of South % Corner, Section 1 % Corner, Section 1 % Corner, Section 1 % Corner of South % Corner, Section 1 % Corner of Secti | ed to the face of the post sured to the foundation assured to the foundation applied in restoring or reestablican 1, T21N, R17W  crew from Abonmarche went E721N, R17W, 3.13 chains (206 determine the location of the companion of the foundation of the foundation of the companion of the foundation of the Lake. (The area has been filled to the foundation of the companion of the companion of the companion of the foundation of the Lake. (The area has been filled to the foundation of the foundation of the Lake. (The area has been filled to the foundation of the companion of the compan | region of the corner:  B as a careful and faithful  B as a careful and faithful |
| Note: The corner is 206.58 ( Note: The corner is ±6" belo Note: The corner is in Seng (  | w grade.   |  | d from their office for admittance.   |

FORM RHIRANDRY MCHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1
REVISED MAY 14,1