DEC 0 9 1999

REVISED OCT., 1995

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

SECTION

For corners in REGISTER'S OFFICE <u>Manistee</u> Located In: Corner Code # MANISTEE COUNTY 99-225 at 1.35 ρm JUL 22 1999 (County) 1. Public Land Survey T<u>22N</u> R<u>17W</u> M-07 MC Witness Cor. to rborahDix Meander Cor. N. of E1/4 Cor. REGISTER OF DEEDS 2. Property Controlling R of Sec. 24 in Section 3. Miscellaneous S T R Register of Deeds Stamp & File Number Property in Sec. S T R 005 4. Lot No. Recorded Plat 5. Private Claims I, Anthony M. Slawinski, in a field survey on <u>June 7</u>, 19 99 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below: NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate. Description of original monument and accessories and/or subsequent restoration: M-07MC Witness Corner to North of East 1/4 Corner of Section 24, T22N, R17W Set by John Brink in 1837 by going North from the Southeast Section Corner of Section 24, T22N, R17W, 70.79 chains until the line intersected the West margin of Lake Michigan, Set Post 1. S 6 1/2° W 24" Hemlock 36 links (23.76') (Gone) 2. S 821/2° E 20" Black Oak 18 links (11.88') (Gone) Plat of Manistee Dunes, 1964 Liber 5, Page 9 Survey Certificate by Bruning 1972 (No withs) Survey Certificate by Slawinski 1979 (No W:#5) Sketch by Slawinski 1979 (No withs) ratified by the Manistee County Peer ਰ Undated Sketch by Bruning (No wi井s) ď. Field notes by Abonmarche 1999 Ω Description of corner evidence found and/or method applied in restoring or reestablishing corner: M-07MC Witness Corner to North of East 1/4 Corner of Section 24, T22N, R17W On June 7, 1999, I Anthony Stawinski with a crew from Abonmarche, measured North along the East line of Section 24, T22N, R17W, until we came to the top of the bluff overlooking Lake Michigan. We set a Witness Corner to the Meander Corner at this location because of the steep bluff down to Lake Michigan. Also, the position of the original corner is now in Lake Michigan. The Witness Corner is 325' North on line from the Property Controlling Corner Set on this line. the state of the South of the position of the original meander corner. I found no evidence to dispute the The Witness Corner is location of this corner. 444.22' 6 6 6 7 C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: country (being sar M-07MC Witness Corner to North of East ¼ Corner of Section 24, T22N, R17W On June 7, 1999 I set a Manistee County Monument on the bluff overlooking Lake Michigan, and is accepted as a careful 22 5 and faithful re-establishment of the original corner, and witnessed by: Ω amended, 3. S 15° W 57.95' 6" Red Pine set 60d on East side of tree **eccording** 4. S 07° E 24.14' Flag Pole (Measured to the face of it) 5. S 65° E 67.30' Southwest corner of house (measured to the foundation) 6. N 50° E 67.30' Northwest corner of house (measured to the foundation) Note: ±150' to the waters edge. Note: the corner is 1587.92' North of the East ¼ Corner of same section. OF MICH ANTHONY SLAWINSKI SURVEYOR -2-99 Surveyor's Michigan License No. 13597 13597 AN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14,1975 REVISED JAN., 1983 LAND