white it is

## REMONIBURE MECOSTA COUNTY REMONUMENTATION PROGRAM

## **CORNER APPROVED BY PEER GROUP ON SEPTEMBER 12, 1997**

NOV 1 8 1997

LAND CORNER RECORDATION CERTIFICATE

STATE OF PRAHIGAN COUNTY OF MEEDSTA RECEIVED FOR RECORD

	 •.,	10.00

COMMISSION		Filing Requirement of Act 74, Mich. P.A. 1970			RECEIVED FOR RECORD							
For corners in  MECOSTA  (County)	Located In:	Corner Code #					P2:2					
Public Land Survey	T 15N T	R 10W G-04 R R	REGISTER OF DEEDS									
<ol> <li>Property Controlling in Section</li> <li>Miscellaneous Property in Sec.</li> </ol>	TS TS T	R R Regi	iste	ster of Deeds Stamp & File Number								
4 Lot No, R 5. Private Claims			1 A	. В	C D	E F	G Н	IJk	( L			
			2	6	5	4	3	2	1			
do hereby certify that under	r_requirements of P.A	in a field survey on JUNE 19, 1997, 74, Michigan P.A. of 1970, the corner points mentioned in the regulations and rules therefore as required in the	4	7	8	9	10	11	12			
current manual of survey in Management or by a decree	nstructions of the Uni e of a Court of Law_a	ited States Department of the Interior, Bureau of Land	6	18	17	16	15	14	13			
Court of Law; established expressed below:	e with the rules of the ed, re-established,	e Michigan Board of Land Surveyors or by a Decree of a monumented, re-monumented, recovered, found as	8	19	20	21	22	23	24			
			10	30	29	28	27	26	25			
NOTE: Only one corner	may be recorded o	on this certificate.	11 12	31	32	33	34	35	36			
COMMON TO SECTIONS 9,	R E. VANNESS, SET 10, 15, AND 16,	daccessories and/or subsequent restoration:  I POST IN FEB. 1838, CORNER POST PLACED 40.00 AND WITNESSED: BEECH 20" N42°W 8 1 BEECH 8" S13°W 25 1  DOK NO.1, PAGE 140 - 141, BY L.W. JUNE, CITY S	LINI LINI	KS KS (	(5.28 16.50	FEET)						
CORNER RECORDED AS PER NOTED AS, "FOUND 3/4"	R P. A. 74 OF 197 ID PIPE AT INTER	70, BY DUANE F. WOOD, P.S. 24625, ON SEPT. 24, RSECTION OF FENCES", AND WITNESSED: 8" ELI 10" PII 3" IR	ME		N LIBI N50°W N40°E S50°E	35. 80.	. 6 . 0	92, An	4D			
CORNER CALLED FOR IN S NOTES CORNER AS, "3/4"	SURVEY FOR CITY C 'PIPE", AND WITK	OF BIG RAPIDS JOB NO. 91014, BY, DUANE F. WOOD, KESSED: 8" ELM N50°W 35.6 10" PINE N40°E 80.0 3" IRONWOOD S50°E 73.1	, Р	.s. 2	4625,			1991,	DNA			
	A n D	PROVED BY MECOSTA CO. PEER GROUP  ACCORDANCE WITH P.A. 345 of 1990  TAIRMAN  ATB  SEPT. 12, 1997	ONWO	OCD	N50°W N40°E S50°E	35. 80.	0					
ROW - EAST)	PE, PROTRUDING 4	and/or method applied in restoring or reestablishir " ABOVE GROUND AT FENCE CORNER, (FENCE - NORTH	н, s	SOUTH,	, AND			CCUPTI	:ON			
G - 4 1/4 CORNER COMM	iment for corner at On to sections 9	nd accessories established to perpetuate locating t	lhe	positi	on of t	he cor	ner:					

1" X 20" IRON PIPE, AND IS ACCEPTED AS A CAREFUL AND FAITHFUL RE-ESTABLISHEDMENT OF THE POSITION OF THE ORIGINAL CORNER.

CORNER.
REMOVED THE IRON PIPE AND PLACED IN THE SAME POSITION A STANDARD MECOSTA COUNTY REMONUMENTATION MONUMENT, PROTRUDING 2" ABOVE GROUND, AND WITNESSED:
FOUND 16d NAIL IN EAST SIDE OF 8" ELM
FOUND 16d NAIL W/TAG NO. 17741 IN N.W. SIDE 12" WHITE PINE
FOUND 16d NAIL IN N.E. SIDE OF 6" IRONWOOD
FOUND 16d NAIL IN S.W. SIDE OF 10" ELM
FOUND 16d NAIL IN S.W. SIDE OF 10" ELM
FOUND 16d NAIL IN S.W. SIDE OF 10" ELM

ASSISTANCE COUNTY REMONUMENTATION MONUMENT, PROTRUDING AZ. 4°, 59.60 FEET
FOUND 16d NAIL IN S.W. SIDE OF 8" IRONWOOD
AZ. 140°, 73.00 FEET
FOUND 16d NAIL IN S.W. SIDE OF 10" ELM
AZ. 318°, 35.72 FEET

ames J. Knapp Surveyor's Michigan License No.

SEPTEMBER 8

ADAPTED FOR WORD ENTOSED IN CHILD

OF CIENIS

11BER 100 PAGE 293

Date \_