

Land Corner Recordation Certificate
Attachment B to 2018 Annual Grant Agreement
Authority: MCL 54.205 and R54.202

This form is **ONLY** for corners filed under the 2018 State Survey and Remonumentation Grant Agreement

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2018 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Midland Co.

Jasper Twp.

Corner Type	Survey Township	Corner Code
Original Public Land Survey Corner	T 13N R 2W	G3
• MCL 54.202(g)	T R	
• MCL 54.262(g)	T R	
Property Controlling Corner	S T R	
• MCL 54.202(i)	S T R	
• MCL 54.262(h)	S T R	
Protracted Public Land Survey Corner	T R	
• MCL 54.202(k)	T R	
• MCL 54.262(i)	T R	

1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
2	6			5		4		3		2		1		2
3														3
4	7			8		9		10		11		12		4
5														5
6	18			17		16		15		14		13		6
7														7
8	19			20		21		22		23		24		8
9														9
10	30			29		28		27		26		25		10
11														11
12	31			32		33		34		35		36		12
13														13
	A	B	C	D	E	F	G	H	I	J	K	L	M	

Part A: Corner(s) History

- G3** – Corner common to Sections 3, 4, 9 and 10, T13N, R2W –
- **1831**- GLO – C. W. Christmas
 - 1) Tamarack 13" North 6 L.
 - 2) Tamarack 16" S08°W 15 L.
 - **1853** – GLO – Resurvey – A. Burt – Old Corner
 - 3) Maple 6" S11½°E 19 L.
 - 4) W. Pine 7" N16½°E 38 L.
 - **1902** – CSR – P. 136 – F. T. Gibbs – Sec. 9 Survey – Set piece of pine root. No timber near for bearing.

Part B: Surveyor's Report on Perpetuation or Monumentation of Corner(s)

G3 – Corner common to Sections 3, 4, 9 & 10, T13N, R2W – No GLO evidence found. Based on retracement of Gibbs survey dug 3' x 3' area in sawgrass and willow marsh and find 3 ½" x 1.3' long pine stake bottom with axed point. Also found a 5/8" rebar of unknown origin is N42°26'E 18.17' from stake point. Accepted pine stake point per Gibbs as the best available evidence of the position of the original corner.

Part C: Field Evidence of Perpetuation or Monumentation of Corner(s)

G3 – Corner common to Sections 3, 4, 9 and 10, T13N, R2W –
Set stamped 4" DNR Aluminum Cap on 1" x 5' long galvanized iron pipe in place of pine stake point – Up 1'±.
Reset stake point on N side of DNR monument as memorial. Set Blue Composite Post 1' SW
S17°E 25.79' to set ½" x 24" long iron rebar
S60°E 17.63' to set ½" x 18" long iron rebar
N84°W 12.68' to set ½" x 18" long iron rebar
N42°26'E 18.17' to found 5/8" rebar

Date of Observation	Latitude	Longitude	Datum and Adjustment Year	Epoch Date
Sept. 25, 2017	N43°32'18.5536"	W84°32'54.4607"	NAD83(2011)	2010

2 Static GNSS Baselines from 2 local OPUS Base stations adjusted by least squares.

I, Craig W, McVean, in a field survey on Sept. 25, 2017 certify under the requirements of the State Survey and Remonumentation Act, 1990 PA 345, MCL 54.261 to 54.279, and the Corner Recordation Act, 1970 PA 74, MCL 54.201 to 54.210d, that the corner(s) identified and described hereon has been perpetuated or monumented as described in Parts A, B, and C above, pursuant to the laws and rules of the State of Michigan.

Craig W. McVean

Craig W. McVean

12/11/2018

Date

Professional Surveyor's License No.: 39088

Michigan Dept. of Natural Resources,
8015 Mackinaw Trail, Cadillac, Michigan, 49601



I, Brian D. Ferguson, state that the corner(s) identified and described hereon and perpetuated or monumented as described in Parts A, B, and C above was presented to and reviewed by the Peer Review Group on August 29, 2018 and is accepted for filing in the Midland County Remonumentation Program.

Brian D. Ferguson

Brian D. Ferguson

Date

Professional Surveyor's License No.: 26454