

For corners in

Midland  
County)

Located In:

REMONUMENTATION

Corner Code ##

1. Public Land Survey

T<sup>14</sup>N R<sup>2</sup>W

A-6

T R

T R

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN  
HIGHLAND COUNTY  
REMONUMENTATION & FILED

30 NOV 93 3:09 P.M.

BEVERLY J THAYER  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, Norman C. Caldwell, in a field survey on May, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

(A-6) Closing West 1/4 Cor. Sec. 18, T14N-R2W

This position not established by original government survey.

L.C.R.C. by P. Lapham, Recorded in Bk. 1 P. 528, Set 13mm Rerod by single proportionate Meas't: S45°E 16.12M 12CM Maple; S45°W 13.29M 18cm Tri. Maple; N60°E 26.67M 30.5cm Balsam Fir; South 21.446M E 1/4 Cor. Sec. 13, T14N-R3W, 26mm pipe.

L.C.R.C. by T. Mueller, Recorded in Bk. 1 P. 603, Found 13mm Bar w/cap by Lapham: SSW 31.67M P. Pole; SE 16.191M 20cm Maple; South 21.443M E 1/4 Cor., Sec. 13, T14N-R3W; East 10.06M 13mm x 45cm Bar w/cap. (Survey in L. 2, P. 972)

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(A-6) Closing West 1/4 Cor. Sec. 18, T14N-R2W

Found 13mm Re-Rod w/cap per Bk. 1 Pgs. 528 & 603. Placed Mon. Box & cap #12018 on iron rod.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(A-6) Closing West 1/4 Cor. Sec. 18, T14N-R2W

Found 13mm Iron Rod per Bk. 1 Pgs. 528 & 603, and is accepted as a careful and faithful reestablishment of the position of the original corner. Placed Mon Box & Cap #12018.

N60°E 26.672M 30cm Hemlock(R)  
S42°E 16.185M 15cm Maple(R)  
South 21.458M (M-6) T14N-R3W(R)  
S70°W 18.246M 28cm Maple(R)  
S20°W 31.689M P. Pole (R)



Signed by

*Norman C. Caldwell*

Date

16 NOV 93

Surveyor's Michigan License No.

12018