PPROVE _ _ .. JD CORNER P.A. 345 OF 1990 MIDLAND COUNTY

SURVEY & REMONUMENTATION

4/23/96 980

REMON. COR. G-1, GENEVA TWP. 00T 0 3 1996

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 COMMISSION

| | rners in | | , | | |
|--|--|--|---|--|----------------------------------|
| <u>Midlan</u> | (County) | Located in: | Corner Code # | 252 | |
| 1. Pub | olic Land Survey | T <u>15N</u> R <u>2W</u> TR | G-1 | STATE OF MICHIGAN MIDLAND COUNTY | |
| | | T — R — | ***** | REMONUMENTATION & FILE | Þ |
| | perty Controlling ection | \$T_R \$T_R | · | 22 AUG 96 8:03 A.M. | |
| 3. Mis | cellaneous perty in Sec. | S T R S | | BEVERLY J. THAYER | |
| | . • | | | Register of Deeds Stamp & File Number (NEDIS) ER UF JEEUS | |
| | No, Reco ate Claims | rded Plat | | | |
| that und lines 1 a in the cu interior, corner p of the Mi monume | er requirements of P.A. and 2 above were in or urrent manual of surve Bureau of Land Mana points mentioned in lic ichigan Board of Land ented, re-monumented Not more than 4 recorded on this | | r points mentioned on therefore as required Department of the Law and/or that the mance with the rules of Law; re-established, w: | A B C D E F G H I J 2 | 1—12- 1—13- 3—24- 5—25- |
| | _ | I monument and accessories a | nd/or subsequent resto | | TE STORY |
| G-1 | Corner common to S | Sections 3 and 4 on North Town Line | | RODNE | |
| | Survey by Governme | ent, 1830's, set wood post | | CLAYPO LAND | Or 1 |
| | Survey by F. Gibbs, | 1900 & 1903, used corner | | AURVEY No. | 3 |
| | Survey and LCRC by | P. Lapham 1971, found 5/8" Iron rod | | 2020 | illi |
| WITNE | | sses from above surveys and Li nted to peer review committee | | | |
| B. Des | cription of corner | evidence found and/or method | d applied in restoring o | r reestablishing corner: | |
| G-1 | | Sections 3 and 4 on North Town Line ys by F. Gibbs and P. Lapham and LC | CRC by P. Lapham. | | |
| Corner | <u>6- /</u> was ápproved | d for remonumentation at a Pe | er Review Committee M | leeting on <u>4/23/96</u> . | |
| C. Des | scription of monun | nent for corner and accessories | s established to perpetu | uate locating the position of the corner: | |
| G-1 | Corner common to S | Sections 3 and 4 on North Town Line | | | |
| | Found rod, replaced LCRC by P. Lapham | with 5/8" rod and brass cap stamped; and is accepted as the best available | Midland Co. Remon Cor. Person Cor. Person of | S 29241 in mon box per surveys by F. Gibbs and P. the accepted corner. | Lapham a |
| | N 50 Deg W, 49.41', S 45 Deg W, 67.17', N N 50 Deg E, 95.41', r N 10 Deg E, 26.61', r East, 49.16' to G-13, | | | | |
| Signed | - | | Da Da | ate <u>5-10-96</u> | · |
| Survey | or's Michigan Lice | nse No. <u>29241</u> | Form approved | by Michigan State Board of Land Surveyors, Jan. 2 Revised May 14 Revised Jan., | 4, 1971 |