

APPROVED LAND CORNER
P.A. 345 OF 1990
MIDLAND COUNTY

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

288

For corners in

MIDLAND
(County)

Located In:

Corner Code #

1. Public Land Survey

T 16N R 1E G-6
T R
T R
T R
S T R
S T R
S T R
S T R

2. Property Controlling
in Section

3. Miscellaneous
Property in Sec.

4. Lot No. , Recorded Plat

5. Private Claims

STATE OF MICHIGAN
MIDLAND COUNTY
REMONUMENTATION & FILED

27 NOV 96 2:54 P.M.

BEVERLY J THAYER
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

I, PAUL B. LAPHAM, in a field survey on OCTOBER, 19 95 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
1832 PARKE
SET 1/2" MILE POST
WIT.-HEMLOCK 12" N45°W 26 LKS.
HEMLOCK 9" S41°E 12 LKS.
5-15-72 WHITTIER L.C.R.C.
FOUND HARROW TOOTH WITH CROCKERY
AROUND & SHARPENED POST BESIDE.
3' DEEP. RAISED WITH 3/4" PIPE.
SAME WITNESSES AS ABOVE.

12-09-93 JONES
WIT.-N85°E, 62.72' - NAIL IN 12" ASH
N40°W, 61.22' - NAIL IN T.P. STUB
S60°W, 96.80' - CENTER 12" MAPLE
S30°W, 128.50' - CENTER 10" MAPLE

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 3/4"x16" PIPE OVER A HARROW TOOTH AND CROCKERY AT 3' DEPTH. FOUND O.B.T.'S.

Corner, G-6 was approved for remonumentation at a Peer Review Committee Meeting on JAN 12, 1996

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 3/4"x18" GAS PIPE WITH BRASS CAP STAMPED "MIDLAND CO. REMON. COR. PS 9433" OVER HARROW TOOTH & CROCKERY.
ACCEPTED AS BEST AVAILABLE EVIDENCE OF PERETUATION OF C.S.R. CORNER.

WITNESSES:
N85°E, 62.72' - NAIL & TAG IN 14" ASH (OBT)
N40°W, 61.22' - NAIL & TAG IN T.P. STUB (OBT)
N65°W, 89.45' - NAIL & TAG IN 18" MAPLE (OBT)
S60°W, 96.80' - NAIL & TAG IN 13" MAPLE (OBT)
S30°W, 128.50' - NAIL & TAG IN 12" MAPLE (OBT)

Signed by Paul B. Lapham
Surveyor's Michigan License No. 9433

Date 10-4-96

