

Land Corner Recordation Certificate
Attachment B to 2016 Annual Grant Agreement
 Authority: MCL 54.205 and R54.202

This form is **ONLY** for corners filed under the 2016 State Survey and Remonumentation Grant Agreement

Filing Requirement: MCL 54.268(2)(a), 54.268(2)(d), 54.201 – 54.210d and 2016 State Survey and Remonumentation Grant Agreement

Notes:

- No more than two Original Public Land Survey Corners can be recorded on this certificate
- If a corner reported hereon is common to two or more survey townships, each Town, Range and Corner Code for the corner may be identified on this certificate
- If a corner reported hereon is common to two or more counties, each county may be identified on this certificate and a copy of this certificate filed with the Register of Deeds in each county

For corner(s) in: Midland County

Edenville & Jerome Twps.

Corner Type	Survey Township				Corner Code															
Original Public Land Survey Corner	T	16N	R	1W	C13	1	A	B	C	D	E	F	G	H	I	J	K	L	M	1
• MCL 54.202(g)	T	15N	R	1W	C1	2	6		5		4		3		2		1		2	
• MCL 54.262(g)	T		R			3														3
	T		R			4	7		8		9		10		11		12		4	
	T		R			5														5
Property Controlling Corner	S		T		R		6	18	17	16	15	14	13	12	11	10	9	8	7	6
• MCL 54.202(i)	S		T		R		7													7
• MCL 54.262(h)	S		T		R		8	19	20	21	22	23	24	25	26	27	28	29	30	8
	S		T		R		9													9
Protracted Public Land Survey Corner	T		R			10	30	29	28	27	26	25	24	23	22	21	20	19	18	10
• MCL 54.202(k)	T		R			11														11
• MCL 54.262(i)	T		R			12	31	32	33	34	35	36	37	38	39	40	41	42	43	12
	T		R			13														13

Part A: Corner(s) History

C13 & C1 – 1830 – GLO – R. Clark, Jr. – Set Post

- 1) Pine 18" N17°E 14½ L.
 - 2) Hemlock 9" N56°E 12 L.
- **1852 – GLO – T15N, R1W Subdivision – A. Burt – Correct S. from post**
- 3) W. Pine 5" S38°W 17 L.
 - 4) W. Pine 5" S10°E 26 L.
- **1911 – CSR, p. 313 – F. J. Gibbs- Sec.31 petition survey**
 Set W. Oak post in place of old corner post. West 40.17 to 'B13' & 77.60 to 'A13'. Distance north 40.00 to 'C12' and 80.00 to 'C11'.
- **No Date – Ayres Assoc.- Working drawing- Sec. 6, T15N, R1W-Distance to 'A1'- 5092.20'; distance to 'C3'- 5232.37'; distance to 'B1'- 2636.40'.**
- **1993 – Record Survey-L. 5, P. 73 – J. L. Jones(PS#19838)-Sec. 31 T16N, R1W survey. Shows "Township line established in 1985 survey. No monument shown. Distance north to 'C11' - 5263.50'; distance west to 'A13'- 5092.20'**
- **2001 – Unrecorded Survey – Mid-Michigan Eng. & Surveying – Job #01063- Sec. 6 survey**
 Set iron at retracement of survey by Ayres & Assoc. N89°31'16"W 2636.29' to 'B1' & 5091.99' to 'A1'.
- 5) Set nail 4" W. Pine S63°W 24.83'
 - 6) Set nail 20" Maple N5°W 53.94'
 - 7) Set nail 4" W. Pine N73°E 35.88'
 - 8) Set nail 4" Oak S6°E 21.79'

