

# LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. PA 1970

For Corners In:

Midland  
(County)

Located In

Corner Code #

1. Public Land Survey	T		R	
	T		R	
2. Property Controlling in Section	S 19	T 16N	R 2E	1
	S 19	T 16N	R 2E	4
3. Miscellaneous Property in Section	S	T	R	
	S	T	R	

4. Lot No: Recorded Plat:

5. Private Claims:

I, Craig W. McVean, in a field survey on November 18, 2009 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

**NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

1 - None

4 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

1 - W 1/16 Corner common to sections 18 & 19,  
- Set a stamped 2" Aluminum cap on 5/8" x 34" rebar per Standard BLM procedure. Centerline of E-W bit road is 5' N.

4 - NW 1/16 Corner Section 19 - Set a stamped 2" Aluminum cap on 5/8" x 34" rebar per Standard BLM procedure

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1 - Stamped 2" Aluminum Cap on 5/8" x 34" rebar

4 - Stamped 2" Aluminum Cap on 5/8" x 34" rebar

N58°E 79.02' to set nail & tag in S side 9" Ash  
S50°W 61.57' to set nail & tag in NW side 13" Oak  
N24°W 56.25' to set nail & tag in E side 8" Oak  
South 33.00' to set 2" Aluminum cap on 5/8" x 34" rebar on-line with Blue Carsonite Post and location tag.

S47°E 21.56' to set nail & tag in NE side 5" Oak  
S04°E 47.93' to set nail & tag in E side 6" R. Maple  
N81°W 25.23' to set nail & tag in N side 9" Oak  
N02°W 22.71' to set nail & tag in W side 8" R. Maple  
Set Blue Carsonite Post with location tag 1' Southwest

Signed by:

Craig W. McVean

Date:

1/13/2010

Surveyor's Michigan License No.:

39088