

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A., 1970For corners in
MONROE (58)

(County)

Located In:

Corner Code #

WHITEFORD TWP.

T 8 S R 6 E

I-2

1. Public Land Survey

2. Property Controlling
in Section

3. Miscellaneous

Property in Sec.

4. Lot No. _____, Recorded Plat _____

5. Private Claims _____

S T R
S T R
S T R
S T R

1999 Remonumentation Program Corner

I, George B. Warnke, Jr., in a field survey on September 7, 1999 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and / or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1820 - GLO - Joseph Wampler - North / Between Secs. No. 2 & 3 /

32.00 / enter prairie /

34.50 / a Run 6 lks. side, course S. East /

40.00 / Set the 1/2 mile post from which a

W. Oak 18 ins. dia. bears N26E 1.12 lks. (112 links) dis. & a

W. Oak 23 ins. dia. bears S35E 1.87 lks. (187 links) dis.

1890 - Willis Baldwin - notes - Stone at 1/4 corner E. side - Burr Oak N 7-1/2°E 173

1893 - A. F. Winney - notes - E / 1/4 Post / W. Oak 26" N 7-1/2°E 1.76

8/1940 - A. J. Marino section corner notes - F. Stone -

SE 127.25' NW Cor. House & NE 100.25' SE Cor. House

1957 - MSHD - Stone 8" deep -

12" Boxelder N44°E 48.60' & 8" Boxelder S33°E 82.84' & Tel. Pole N58°W 40.20'

1972 - G. B. Warnke - Job #72-3-17 - Liber 617, Page 956 - Fd stone 10" DP. / set bolt at surface -

N44°E 48.00' shiner SW side 18" Box Elder & S70°E 60.00' shiner N'ly face pow. pole & N55°W 42.00' shiner SW face tel. pole

9/1978 - G. B. Warnke - Job #78-212 - I. bolt over stone - 3 witnesses which compare to GBW 1972

10/1978 - Case & Fleck - notes - FD. RD. HD BOLT

1/1981 - G. B. Warnke - LCRC, Liber 2, Page 451 (ref. Job #81-14) - Bolt over stone 10" deep

N44°E 47.90' nail & shiner SW side of 18" Box Elder & S70°E 60.00' nail & shiner N'ly face of power pole &

N55°W 42.00' nail & shiner SW face of tel. pole & N35°E 92.13' nail & shiner W. face 24" Cottonwood

2/1990 - G. B. Warnke - Job #89-777 - Found 1" Round Headed R.R. Bolt 2' Deep Raised to Surface with Nail & Washer -

S70°E 60.08' shiner N'ly face power pole & N55°W 41.90' shiner SW face telephone pole &

N35°E 120.60' NW cor. Res'd #5896 & S50°E 127.63' NW cor. Res'd #5897

6/1991 - G. B. Warnke - LCRC, Liber 3, Page 137 (ref. Job #91-0236) - Found nail & washer over bolt over stone -

S70°E 60.08' nail/shiner N. face elec. pole & N55°W 41.90' nail/shiner SW face tele. pole &

N35°E 120.60' NW corner res'd #5896 & S50°E 127.63' NW corner res'd #5897

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner is located in the intersection of School & Bacon Roads / in tarby pavement

Corner based on our last use in 1991. Stone is tracked since 1890.

9/7/1999 - Dug 24" diameter hole. Found concrete nail & washer over 12" x 3/4" round head bolt over large granite stone 18" deep with old

railroad spike on top of stone. Broke away northeast quarter of the stone. Set 5/8" x 12" rebar at 30" deep. Set 1" x 36" pipe over rebar.

Bolt stands on east edge of 1" pipe. Set in monument box at surface. Set brass remonumentation cap on 1" pipe. All witnesses okay from 1991.

RATIFIED BY PEER GROUP, PA 345 OF 1990, MONROE COUNTY, MICHIGAN, DATE 7/13/1999, COUNTY REP. [Signature]

Corner is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set brass remonumentation cap on set 1" x 36" pipe over set 5/8" x 12" rebar in set monument box & Witnesses:

South 70° East 60.08 feet to nail/shiner in north face of electric pole

North 55° West 41.90 feet to nail/shiner in southwest face of telephone pole

North 35° East 120.60 feet to northwest corner res'd #5896 - stone foundation

South 50° East 127.63 feet to northwest corner res'd #5897 - 2 story section

4 feet west of centerline of pavement

Signed by

Surveyor's Michigan License No.

19474

Date September 8, 1999

APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983
REVISED OCT., 1994

LIBER

4 Tab 507