

1893

COMMISSIONER

JOB NUMBER: 93300

SHEET NO. : 1-410

For corners in

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

MARQUETTE  
(County)

Located In:

Corner Code #

## 1. Public Land Survey

T45N R25W

MC M-10/11

T45N R24W

MC A-10/11 ✓

T R

T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

## 4. Lot No. , Recorded Plat

## 5. Private Claims

I, GERALD W. CARLSON, in a field survey on Thursday, December 23, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

## A. Description of original monument and accessories and/or subsequent restoration:

MC M-11: Meander Corner North of the Section Corner common to Sections 25 & 36, T45N-R25W and Sections 30 & 31, T45N-R24W. 1844; William A. Burt's original survey notes describe the corner monument as a wood post referenced by:  
22" White Pine N45W, 22 1  
(North shore of Bass Lake)

1939 - Map of Lot 1 Section 30 T45N-R24W by R.A. Brotherton indicates a 1" iron pipe set at the South 1/16 corner, also indicates 15.8 ft. further South to MC. The 1/16 corner and the MC are relatively close on the North side of Bass Lake. No corner accessories given. A distance between the 1/4 corner common to Sections 25 & 30, as shown as 1320 ft.

## B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1993 - Found 1" pipe 0.9 ft. high. Distance North measures 1316.20. The distance South across Bass Lake matches R.J. Brotherton's 1954 survey almost exactly. Accepted this as the section line and monumented it as on W.C.M.C. Peer group ratification 12-13-93.

## C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1993 - Replaced iron pipe with a 2 1/8" diameter aluminum pipe capped with a 3 1/4" diameter aluminum tablet Marquette County Survey Monument stamped to identify the corner referenced by nails in:

8" White Birch N09W 7.27 ft.  
6" Balsam S78E 9.91 ft.  
7" Spruce S17E 17.70 ft.  
9" Red Pine N88W 18.91 ft.

Monument is 0.40 ft. above ground, 17.7 ft. North of waters edge of Bass Lake, 12.6 ft. West of the West face of Hines camp #1213.  
No blazes or tags on trees. Bk. 6, Pg. 2

Signed by Gerald W. CarlsonDate 12-28-93Surveyor's Michigan License No. 24589