

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

| FOR CORNERS OF--: | LOCATED IN--: | CORNER CODE NUMBER |
|---------------------------------------|-------------------|--------------------|
| 1. PUBLIC LAND SURVEY | T. 45 N. R. 29 E. | M7 & M8 |
| 2. PROPERTY CONTROLLING IN SECTION | T. N. S. R. E. W. | |
| 3. MISCELLANEOUS PROPERTY IN SECTION | T. N. S. R. E. W. | |
| 4. LOT NO. _____, RECORDED PLAT _____ | | |
| 5. PRIVATE CLAIMS _____ | | |

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Arthur O. Enger do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram—over) were, in a field survey on November 5, 1971, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

Corner M7: White birch post (not found)
W. Birch 6 N68E 33 " "
W. Birch 12 S72W 33 " "

Corner M8: White birch post (not found)
Y. Pine 18 S67W 51 " "
Y. Pine 18 N42E 30 " "

No subsequent monuments found at either corner.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner M7: Re-established by proportionate measurement on line between original section corners 79.93 ch. S and 159.86 ch. N.

Corner M8: Re-established by proportionate measurement on line between original section corners 39.965 ch. S and 199.825 ch. N.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Monuments for both corners: 1" I.D. x 36" iron pipe with 4" aluminum cap.

Witnesses for Corner M7: Red Oak 6 N10W (mag.) 8.9 ft. "S13, NBT"
Red Oak 6 S260W (mag.) 41.0 ft. "S24, NBT"
Red Maple 7 N360E (mag.) 23.2 ft. "S18, NBT"
W. Birch 12 S56½E (mag.) 22.5 ft. "S19, NBT"

Witnesses for Corner M8: Red Pine 6 N190E (mag.) 9.7 ft. "1/4S, NBT"
Red Pine 6 S220E (mag.) 85.3 ft. "1/4S, NBT"
Jack Pine 13 S220W (mag.) 64.1 ft. "1/4S, NBT"

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Arthur O. Enger DATE January 19, 1973

Arthur O. Enger
Michigan Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 13581