

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Marquette

(County)

Located In:

Corner Code #

1. Public Land Survey

T R

T R

T R

S T R

2. Property Controlling
in Section

S 2 T 45N R 29W

S 2 T 45N R 29W

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

5 Aug 10 2004

6 Aug 09 2004

I, Stephan J. Szyszkoski, in a field survey on , 20 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(6-Sec. 2) Northeast 1/16 corner, Section 2. Not established in the original survey.

(5 - Sec. 2) North 1/16 corner, Section 2. Not established in the original survey. The U.S. plat for T45N-R29W implies record protracted distances of 20.00 chains south to Center of Section, and 20.815 chains north to 1/4 corner.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(6-Sec. 2) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

(5 - Sec. 2) Established the corner on the N-S 1/4 line of the Section, 1308.18' north of the unmonumented Center of Section and 1361.48' south of the 1/4 corner common to Section 2 T45N-R29W and 35 T46N-R29W, the distances being proportioned to the record, noted above.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(6) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Blazed, scribed, and set

measuring nails in:

4" J.Pine N49W 28.7' "1/16S BT"

4" W.Pine N53E 48.7' do

5" Poplar EAST 16.0' do

4" Poplar S28E 22.2' do

a 4"x4" treated wood post is adjacent.

Bearings are magnetic. Distances are to nail with tag.

(5) Set 1"IDx32" I.pipe with 4" alum.

MDNR cap. Blazed, scribed, and set

measuring nails in:

9" Maple N32E 17.2' "1/16S BT"

4" Maple S61E 19.9' do

7" Maple S22E 36.3' do

12" Oak N76W 18.2' do

Set sq'd cedar post adjacent. Bearings

are magnetic. Distances are to nail with tag.



Signed by

Stephan J. Szyszkoski

Date

9/2/04

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources, Office of Land and Facilities

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971

Revised May 14, 1975

Revised Jan., 1983

Revised Oct., 1995