SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

MARQUELTE COUNTY	
RECEIVED FOR RECORT	D

1994 DEC 22 AM 11: 24

Patricia	A.	Mone	leus
Patricia REGISTER	0F	DEEDS	on

For corners in	المحمد ما	l Jan	0			Patricia	A. Mo	uleus
MARQUETTE (County)	Located	ı in:	Corner C	ode#		REGISTER	OF DEEC	13 0
1. Public Land Survey	T <u>46N</u> I	R	A-4 M-4	_				δ,
 Property Controlling in Section Miscellaneous Property in Sec. 	S T S T	R R R R			Domina			PAGE 19
4. Lot No , Re	corded Plat				Kegiste	or of Deeds St	amp & r	iie Numbe
5. Private Claims					АВС	DEFG) H I	J K L
					2 6	5 4	3	
I, <u>GERALD W. CARLSON</u> hereby state that under requ	irements of P.A. 74	I, Michigan P.A.	of 1970, tl	ne corner points	3 4 7	-89	10	-1117
mentioned in lines 1 and 2 all required in the current manual of		_			5			
Bureau of Land Management mentioned in lines 3, 4 and 5	or by a decree of a	a Court of Law	and/or that t	ne comer points	6 18	-1716	15	14——13
Land Surveyors or by a Deci	ree of a Court of L			•	8 19	_2021	22	_2324
recovered, found as expressed	below:				9			
	orners, all in the sa	me town and ra	inge, may be	recorded	10-30-	_2928	27	-2625
on this certificate.					11			
A. Description of original n				estoration:	12 31	_32 <u></u> 33	34	-3536
A-4: Corner common to Se 1844: William A. Burt's orig monument as a wood post i	jinal township boun			the corner	RATIFII	ED BY PEEF IS OF 1990	GROUS	
5" S. Pine S39E,		4" S. Pine	N58W,	11L	_Za	my IE	3 <i>uaa</i> a	re
No Date: Cleveland Cliffs co	oordinate data shee	ts, indicate the	corner is dis	tance N00-24-	DATE.	1 10/25	199	
59E, 2636.16' to the North R25W. No monument descr	west section corner	r and distance S			e Southwest	corner of Se	ction 7,	T45N-
1951: A Land Corner Record Division survey crew set a 1 crew, while making a partial given:	I" pipe with a 4" br	ass cap. Delam	eter states:	This Corner was	s established	by the Fores	try Divisi	on survey
8" Jack Pine S06E,	22L	8" Jack Pine	N40E,	19L				
No Date: Marquette County references:	Road Commission	notes indicate t	he corner m		pipe with a 4	l" brass cap v	with the	following
8" Jack Pine \$06E,	22L	8" Jack Pine	N40E,	19L				
B. Description of corner ev A-4: 1999: No original corner 1.6' above ground and stam Distance North is 2636.02',	er evidence found. nped for identification	Found and acce on. No departm	epted a 1 1/4	" outside diame	ter iron pipe		ss tablet	projectin
C. Description of monumer A-4: 1999: Stamped the 1 ground so it now projects 0	1/4" outside diamet	ter iron pipe wit						to the
Established new references:								
7" Jack Pine S27E, 10" Jack Pine S84E.	73.77' 163.17'	6" Jack Pine 5" Jack Pine		137.82' 63.05'				

Green Steel Sign Post w/ Yellow Survey Marker Sign N77W, 4.05' Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tags affixed. T46N-R25W Corner Search Report 99100



Surveyor's Michigan License No. 24589

+/- 150' West of North-South dirt road.

Date_