

# LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

MARQUETTE COUNTY

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY—	T. 46 N. R. 29 W. <input checked="" type="checkbox"/>	H7, 69
2. PROPERTY CONTROLLING IN SECTION—	22, T. 46 N. R. 29 W. <input checked="" type="checkbox"/>	1
3. MISCELLANEOUS PROPERTY IN SECTION—	T. N. R. E. W.	
4. LOT NO. —, RECORDED PLAT —		
5. PRIVATE CLAIMS —		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on see below, 19\_\_\_\_, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and or subsequent restoration:

Corner 1: Not set on original survey nor subsequently apparently.

Corner H7: Original monument and accessories not found.

Corner G9: Original corner not found. Found old post bottom and two stumps that fit for original bearing trees. Also found line tree to the south that matches this location.

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

Corner 1: Established 6-21-82 midway and on line between corners east and west.

Corner H7: Restored 6-21-82 midway and on line between section corners east and west.

Corner G9: Restored 6-29-82 at post bottom.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Corner 1: Set 1" I.D. by 32" Iron Pipe w/4" alum. cap.

8" W. Pine S46W 4.5 ft. 1/16S, BT

6" W. Pine N82E 8.9 ft. 1/16S, BT

7" Maple N10W 15.3 ft. 1/16S, BT

Corner G9: Set 1" I.D. by 32" Iron Pipe with 4" alum. cap.

5" Maple S55W 17.7 ft S28, NBT

8" R. Pine N35E 30.0 ft. S22, NBT

12" R. pine S70E 35.3 ft. S27, NBT

Corner H7: Set 1" I.D. by 32" Iron Pipe w/4" alum. cap.

5" W. Pine S20E 3.4 ft. 1/4S, NBT

8" Maple N57E 21.1 ft. 1/4S, NBT

5" Maple N02W 26.4 ft. 1/4S, NBT

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

(SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

Keith L. Sackett

Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET