

APR 01 1996

JOB NUMBER: 95053
SHEET NO. : 1-621

COMMISSION LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD

1995 DEC 27 AM 7:41

Patricia A. Monley
REGISTER OF DEEDS

For corners in

MARQUETTE
(County)

Located In:

Corner Code #

1. Public Land Survey

T47N R26W

M-6

T47N R25W

A-6

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Section

S T R

LIBER

1 PAGE 23

Register of Deeds Stamp & File Number

Lot No. , Recorded Plat

Private Claims

GERALD W. CARLSON, in a field survey on Thursday, November 9, 1995, hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

M-6: Quarter Corner common to Section 13, T47N-R26W and Section 18, T47N-R25W. 1844: William A. Burt's original survey notes describe the corner monument as a wood post referenced by:

6" Fir S50E, 31.1

8" Sugar N23W, 20.1

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995: Found a 4" X 3' high Cedar post w/squared top lying flat on ground @ corner location. Also found a 12" Maple with old healed blazes on all four sides N72E, 3.70' from corner location. Stream line call (Rec. = 176.88' North of Corner) found at 171.2'. Corner position established by single proportion measurement on line between the N.E. and S.E. Corners of Section 13. Distances North and South are 2627.00'.

RATIFIED BY PEER GROUP
P.A. 845 OF 1990

Harry J. Buasme
DATE 11/6/95

Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1995: Set a 2 3/8" O.D. aluminum pipe capped with a 3 1/4" diameter aluminum tablet Marquette County Survey Monument stamped to identify the corner. Monument is flush with ground. Established references using double headed nails in:

6" Hemlock	N21E,	28.64'
9" Maple	S64E,	49.60'
9" Maple	S23W,	10.20'
6" Maple	N49W,	16.44'
Green Steel Sign Post w/Yellow Survey Marker Sign	North,	1.0'

Sk. 9, pp. 61-62.



Signed by *Gerald W. Carlson*

Date 12-15-95

Surveyor's Michigan License No. 24589

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983