For corners in COMMISSION Filing Requirement	CORDATION CERTIFICAT of Act 74, Mich. P.A. 197 Corner Code #	DEC 27 DEC 27 DEC 27 DEC 27
T H T R	. 2	W 7: 45
2. Property Controlling S T R		LIBER 1 PAGE 2 Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat		— A B C D E F G H I J H
5. Private Claims		2 6 5 4 3 2
		3
		4-7-8-9-10-11-
I, GERALD W. CARLSON , in a field survey on Wednesday, Nove	mber 15 , 19 ⁹⁵ ,	5
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 197 in lines 1 and 2 above were in conformance with regulations and rules there	0, the comer points mentioned	6 18 17 16 15 14
manual of survey instructions of the United States Department of	the Interior, Bureau of Land	7
Management or by a decree of a Court of Law and/or that the corner point	nts mentioned in lines 3, 4 and	8 - 19 - 20 - 21 - 22 - 23 -
5 above were in conformance with the rules of the Michigan Board of F Decree of a Court of Law; established, re-established, monumented, re-n	nonumented, recovered, found	9
as expressed below:	•	10 30 29 28 27 26
NOTE: Not more than 4 corners, all in the same town and range,	may be recorded	11 32 33 34 35
on this certificate.	1	13 1 1 1 1
E-2: Quarter Corner common to Sections 4 and 5.1848: John Burt's original survey notes describe the corner monument as a Maple post referenced by: 16" Sugar S62W, 14 1 16" Sugar N62E, 52 1 1892: George Cummings, in Record of Surveys Pg. 213, indicates the corner as being set from stumps of trees identical with bearing trees and agreeing in distance measured North. Corner is 2622.00' North of the SW Corner, and 2571.75' South of the NW Corner of Section 4. No accessories given. B. Description of corner evidence found and/or method applies 1995: Found and accepted a 3 1/2" diameter Brass Cap on a 2 North is 2573.22' and Distance South is 2628.87'.	L. 5, RC Pg. 353, indicated place and had been remone Cleveland-Cliffs to replace survey distances and old a Brass Cap on a 2" pipe 1 P. Pole S54W. 4: C.L. Co. Rd. West, 1: 4" W. Pine S57E, 1: 4" W. Pine N57E, 1: 4" W. Pine N5	1.0' Note: Trees have upper 3.4' and lower notches. 9.8' 8.3' iing corner: East Shoulder of Road. Distance
	•	P.A. 345 OF 1990 Carry Susane DATE 1/13/95
C. Decembring of management for a second and a second as a second	iohod to novembrate to a still	a the position of the source
C. Description of monument for corner and accessories estable 1995: Referenced the found 2" pipe and 3 1/2" diameter Bras Found existing references with old face and butt blazes. Refer W. Pine N59E, 18.48' (18.22' to blaze) (Busson W. Pine S52E, 19.20' (19.95' to blaze) (Busson Established references using new face and butt blazes and displayed W. Pine S39E, 26.09' 5" W. Pine S22E, 48.29' Note: Nailed Survey Marker Sign to tree 15.20' East of corner Bk. 11, PP. 71-72.	s Cap: painted blazes and set dupl ne N.B.T.) ne N.B.T.) uplex nails set in:	
M. Mullanhan	1)	3 - GESSIUNIAL SEE

Surveyor's Michigan License No.____

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983