

JOB NUMBER: 95053
SHEET NO. : 1-643

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Located In:

Corner Code #

MARQUETTE
(County)

APR 6 1 1996
COMMISSION

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD
1995 DEC 27 AM 7:46
REGISTER OF DEEDS
Gerald W. Carlson

1. Public Land Survey

T^{47N} R^{27W}

MC C/D-3 (6)

T
T
T
T

R
R
R
R

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous

S T R

Property in Section

S T R

#6

LIBER 1 PAGE 25
Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, GERALD W. CARLSON, in a field survey on Wednesday, November 29, 1995, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

MC C/D-3: Meander Corner West of the Quarter Corner common to N-N.W. 1/16 Corner of Section 8 is 267.3', and West to to Sections 5 and 8. 1848: John Burt's original survey notes N.W. Corner Section 8 is 1598.5'. N-N.W. 1/16 Corner pro-rated on line between West Meander Corner and N.W. Corner Section 8. Distance East to prorated 1/4 Corner is listed as 1114.00'. No accessories given.

18" Tamarack S71W, 73 l

10" Spruce S45W, 50 l

1892: Cummings, in Record of Surveys Pg. 219, indicates the East and West Meander Corners set from stumps with government marks on them, and the North 1/4 Corner pro-rated on line between them. Distance West from West Meander Corner

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995: Found and accepted a 12" diameter Cummings monument, 1' below ground and 6" under water. Line call (Rec. = Enter Swamp N & S, 3.12 Ch. West of corner [205.92'] measured @ 260'). Distance East to Meander Corner on East Side of Rock Lake is 1505.46', Distance West to found West 1/16 Corner to Sections 5 and 8 is 267.09', and Distance East to calculated South 1/4 Corner of Section 5 in Rock Lake is 1114.23'.

RATIFIED BY PEER GROUP
P.A. 345 OF 1990

Larry J. Bussame
DATE 12/04/95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1995: Referenced found 12" diameter Cummings monument using duplex nails set in:

9" Spruce S08E, 53.05'

9" Tamarack S17W, 97.70'

5" Cedar S65W, 31.48'

7" Balsam S89W, 35.85'

Green Steel Sign Post w/Survey Marker Sign West, 1.0'

Water's Edge East, 22.5'

Note: Bearing Tress were face and butt blazed, painted, and had B.T. Tags affixed.

Bk. 9, PP. 73-74.



Signed by Gerald W. Carlson

Date 12-20-95

Surveyor's Michigan License No. 24589