

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD

200 DEC 18 PM 12:45

Patricia L. Manley
REGISTER OF DEEDS *dm*

For corners in

MARQUETTE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 47N R 27W

K-5

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

LIBER **R2** PAGE 267
Register of Deeds Stamp & File Number

I, GERALD W. CARLSON, in a field survey on Sept. 13 TH, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

K-5: Corner common to Sections 11, 12, 13, & 14.

1848: John Burt's original subdivision survey notes describe the corner as referenced by:
8" Sugar N52W, 36L 10" Sugar S40E, 48L

1892: Cummings Survey of Section 11 recorded on page 226. Distance West 2566.7'.
Distance North 2602.2'.

1899: Cummings Survey of Section 14 recorded on page 228 indicates the Northeast corner of Section 14. Distance West 2566.7'.

No Date: C.C.I. Coordinate List indicates the coordinates as South 10264.98 and West 10200.88.

1920: R.A. Brotherton's Field Book Notes indicate the Southwest corner of Section 12 as an Iron Southwest of a Transmission Line.

1933: Marquette County Road Commission Notes indicate a mushroom West of Millie Lake set by G.P. Cummings, February, 1900.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

K-5: 2000: No original corner evidence found. Found and accepted a 2" outside diameter pipe with a 1 1/2" diameter mushroom tablet stamped to identify the corner and projecting 0.65' above ground. Also found a 12" dead Maple with an old blaze, due South, 6.0' to the center of the tree.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

K-5: 2000: Accepted found monument as described in part B above. Monument is 0.65' above ground. Referenced by:

11" Maple S57E, 14.18' 7" Maple S03W, 21.83'

7" Maple N71W, 18.03' 4" Maple N30E, 26.21'

Green Steel Sign Post w/ Yellow Survey Marker Sign Due North, 2.75'

Distance East 2656.80', distance West 2567.70'.

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tags affixed.

T47N-R27W Corner Search Sheet 2000035



Signed by

Gerald W. Carlson

Date

12-12-00

Surveyor's Michigan License No.

24589