LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Marquette (County)	Located in:	Corner Code #	W.
1. Public Land Survey	T 48N R 29W	G8 (GCDB 400340)	
2. Property Controlling in Section	S 26 T 48N R 29W S T R	12 (GCDB 540220)	4
3. Miscellaneous Property in Sec.	S T R R		Positive 4D and a
4. Lot No. , Re 5. Private Claims	corded Plat		Register of Deeds Stamp & File Number A B C D E F G H I J K L N
above were in conformance with instructions of the United States a Court of Law and /or that the	74, Michigan P.A. of 1970, the corner regulations and rules therefore as requipely department of the Interior, Bureau of corner points mentioned in lines 3, 4 and of Land Surveyors or by a Decree	fred in the current manual of survey Land Management or by a decree of and 5 above were in conformance with	3 4 2 ey 5 of 6 tb 7
NOTE: Not more than 2 corr on this certificate.	ners, all in the same town and rang		10 30 29 28 27 26 25 11 12 31 32 33 34 35 36
A. Description of original m	nonument and accessories and/or	subsequent restoration:	13

(G8) Quarter corner common to Sections 21 & 22. 1848 - Established by Wells Burt, Deputy, midway and on the Section line between Section corners 40.00 chains north and south. Set cedar post. Sugar 12" S64°E 31 links, Fir 9" N45°W 22 links. Found no subsequent record.

(12-Sec. 26) Center-South 1/16 corner, Sec. 26. Not established in the original survey. 2008 -Established and monumented by Robert Spear PS in conformance with the regulations and rules noted in the certificate, above, applicable to the subdivision of regular sections.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(G8) The original post and accessories were not recovered. Found no evidence of the position of the original corner on the ground. Reestablished the position for the corner midway and on the Section line between Section corners 2636.62' north and south. The position falls at record distance south of a stream noted in the 1848 US notes as "Stream 20 c.N.W." 19.6 chains north of the corner.

(12-Sec. 26) Found a 5/8" rebar with plastic cap "R.Spear PS43069", projecting 3", set firm and in good condition. The position of the monument conforms with a proper subdivsion of this section based upon currently unmonumented J9 and I10 being located midway and on line between respective section corners and the position of corner I9 being that of a 1/2" iron with 1-3/8" flat top noted on an LCRC for I9 recorded by the undersigned, this date. Accepted the monument at this 1/16 corner as a careful and faithful determination of the position of the corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Da	- 1 1 m 14	OFW
Coord. Ref.=NGS PID AA8080: N= 192972.689 m. E= 7925456.741 m.	- UIII	CHIC
igned by Supplied. Date 11/24/2014		STEPHAN J. SZYSZKOSKI
urveyor's Michigan License No. 33986 For the Michigan Department of Natural Resources, Forest Resources Division		SURVEYOR

FORM APPROVED BY MICHIGAN STATE BOARD

AND Revised Jan., 1983

Revised Oct., 1995