

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Marquette (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 16 T 48N R 30W	F6
	S T R	(GCDB 340440)
	S 16 T 48N R 30W	8
3. Miscellaneous Property in Sec.	S T R	(GCDB 320440)
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

I, Stephan J. Szyszkoski, in a field survey on 07/22/14 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(F6) Center of Section 16. Not established in the original survey

(8-Sec. 16) Center-West 1/16 corner, Section 16. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(F6) Corner not previously monumented. Established the position for the corner at the intersection
of straight lines connecting opposite 1/4 corners.

(8) Corner not previously monumented. Established the position for the corner midway and on a
straight line between Quarter corner 1319.18' west and Center of Section 16 1319.18' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(F6) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
10" Sugar N27°E 11.65' mrkd "C1/4 BT"
7" Sugar N81°E 9.7' do
10" Sugar S5°8'E 5.5' do
8" Sugar S29°W 3.05' do
Set s'qd Cedar post adjacent.
E= 7918354.746 N= 197663.932

(8) Set 1"IDx28" I.pipe with 2" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" Sugar N81°E 17.0' mrkd "1/16S BT"
9" Maple S52°E 6.05' do
8" Maple S26°W 14.45' do
7" Sugar N14°W 7.4' do
Set sq'd Cedar post adjacent.
E= 7917952.732 N= 197663.985

Bearings are magnetic. Coordinates are MCS83 in meters (NAD83(2011) Datum).
Coord. Ref.=NGS PID AA8080: N= 198400.952 m. E= 7925456.741 m.

Signed by Stephan J. Szyszkoski Date 11/12/2014
Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	16		17		18		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

