

APR 01 1996

LAND CORNER RECORDATION CERTIFICATE
COMMISSION Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MARQUETTE
(County)

Located in:

Corner Code #

1. Public Land Survey

T^{48N} R^{27W}

M-9

T 48N R 26W

T R

T R

T _____ R _____

T R

T _____ R _____

2. Property Controlling in Section

S _____ T _____ R _____

S _ _ T _ _ R _ _

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims

GERALD W. CARLSON in a field survey on Monday, December 11 1995

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-9: Section Corner common to Sections 24 and 25, T48N-R27W 1940: B. Schjonberg in MCRC F.B. #701 indicates the corner and Sections 19 and 30, T48N-R26W. 1844: Austin Burt's original survey notes describe the corner monument as a wood post referenced by:

8" Sugar S33W,	66 1	1940: B. Schjonberg in MCRC F.B. #701 indicates the corner as a Square Wooden Stake. He found the remains of a 10"-
7" Sugar N66W,	45 1	12" Sugar S33W, 43.0' from the stake. Tree was still standing, but main trunk of tree had rotted and fallen to the ground. Could not find any trace of Sugar 7" N66W, 45 1.

No Date: The corner is shown on an unidentified map recorded in L. 328, Deeds Pg. 324.

No Date: MCRC F.B. #654 indicates the corner as a Square
Wooden Stake.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995: Found and accepted a 1" O.D. Iron Pipe, 1.33' above ground, next to a 4' high Squared Wooden Post. Distance North is 2630.30' and Distance South is 2624.95'.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1995: Set a 2 3/8" O.D. aluminum pipe capped with a 3 1/4" aluminum tablet Marquette County Survey Monument over the top of found 1" iron pipe, 1.0' above ground, and stamped to identify the corner. Established references using set duplex nails in found N.B.T.'s, and a set duplex nail in a newly established N.B.T.:

13" Poplar S03W, 19.81' (Found N.B.T.)

9" Maple S27W, 32.45'

10" Maple N85W, 26.45' (Found N.B.T.)

7" Maple N30W, 20.69' (Found N.B.T.)

Green Steel Sign Post w/Survey Marker Sign N66E, 1.71'

Note: Bearing trees were face and butt blazed, painted, and had B.T. Tags affixed.

Bk. 10, PP. 67-68.

**RATIFIED BY PEER GROUP
P.A. 345 OF 1990**

DATE _____



Signed by

Date 12-20-95

Surveyor's Michigan License No. 24589

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN. 1983

APR 01 1996

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MARQUETTE
(County)

Located In:

Corner Code #

1. Public Land Survey

T^{48N} R^{27W}

M-9

T 48N R 26W

T _____ R _____

T _____ R _____

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous

S T R

Property in Section

S T R

4. Lot No. _____, Recorded Plat _____

5. Private Claims

GERALD W. CARLSON in a field survey on Monday, December 11, 1995

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Professional Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

M-9: Section Corner common to Sections 24 and 25, T48N-R27W 1940: B. Schjonberg in MCRC F.B. #701 indicates the corner and Sections 19 and 30, T48N-R26W. 1844: Austin Burt's original survey notes describe the corner monument as a wood post referenced by:

8" Sugar S33W, 66 1	as a Square Wooden Stake. He found the remains of a 10"-
7" Sugar N66W, 45 1	12" Sugar S33W, 43.0' from the stake. Tree was still
	standing, but main trunk of tree had rotted and fallen to
	the ground. Could not find any trace of Sugar 7" N66W, 45 1.

No Date: The corner is shown on an unidentified map recorded in L. 328, Deeds Pg. 324.

No Date: MCRC F.B. #654 indicates the corner as a Square
Wooden Stake.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

1995: Found and accepted a 1" O.D. Iron Pipe, 1.33' above ground, next to a 4' high Squared Wooden Post. Distance North is 2630.30' and Distance South is 2624.95'.

**RATIFIED BY PEER GROUP
P.A. 345 OF 1990**

DATE 12/4/95

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1995: Set a 2 3/8" O.D. aluminum pipe capped with a 3 1/4" aluminum tablet Marquette County Survey Monument over the top of found 1" iron pipe, 1.0' above ground, and stamped to identify the corner. Established references using set duplex nails in found N.B.T.'s, and a set duplex nail in a newly established N.B.T.:

13" Poplar S03W, 19.81' (Found N.B.T.)

9" Maple S27W, 32.45'

10" Maple N85W, 26.45' (Found N.E.T.)

7" Maple N30W, 20.69' (Found N.B.T.)

Green Steel Sign Post w/Survey Marker Sign N66E, 1.71'

Note: Bearing trees were face and butt blazed, painted, and had B.T. Tags affixed.

Bk. 10, pp. 67-68.

Signed by _____

Date 12-20-95

Surveyor's Michigan License No. 24589

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS, JAN. 28, 1971
REVISED MAY 14, 1975
REVISED JAN., 1983

