

SURVEY &
REMONUMENTATION

FEB 21 2001

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MARQUETTE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 48N R 26W

B-1

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, GERALD W. CARLSON, in a field survey on October 19 TH, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

B-1: North Quarter Corner of Section 6, T48N-R26W

Corner not established during Original GLO Survey

No subsequent records recovered

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

B-1: 2000: SCA survey crews conducted a thorough search of the area and found no evidence of monumentation except a blue paint line. Corner position was established by proportionate measurement on line between the NW corner and NE corner of Section 6.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

B-1: 2000: Set a 5/8" x 18" rebar 3 1/4" diameter aluminum tablet Marquette County Survey Monument stamped to identify the corner. Monument is 0.75' above ground. Monument is drilled and grouted into bedrock. Referenced by:

5"	Maple	S63E,	8.27'	7"	Maple	S09W,	23.34'
12"	Maple	S52W,	25.73'	6"	Maple	N26W,	23.30'

South 1/4 Section 31, T49N-R26W N89°38'47"E, 13.74'

Green Steel Sign Post w/ Yellow Survey Marker Sign N08E, 4.30'

Distance East 2618.33', distance West 2409.52'

Note: Bearing trees have painted face, butt, and side nail blazes, d.h. measuring nails, and stamped B.T. Tags affixed.

Bk. 15, Pg. 49 T48N-R26W Corner Search Sheet 2000035

MARQUETTE COUNTY
MICHIGAN
RECEIVED FOR RECORD

200 DEC 22 AM 10:18

Patricia A. Monks
REGISTER OF DEEDS *pm*

LIBER **R2** PAGE **283**

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

RATIFIED BY PEER GROUP
P.A. 345 OF 1990

Larry J. Bussone
DATE 11/6/00

Signed by

Gerald W. Carlson

Date

12-19-00

Surveyor's Michigan License No.

24589

FORM APPROVED BY MICHIGAN STATE BOARD OF PROFESSIONAL SURVEYORS



REVISED JAN., 1983
REVISED OCT., 1995