

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

Marquette County		LOCATED IN--:	CORNER CODE NUMBER
FOR CORNERS OF--:			
1. PUBLIC LAND SURVEY	T. 49 N. R. 26 E.		C5, C3, C1
2. PROPERTY CONTROLLING IN SECTION	T. S. R. W.		
3. MISCELLANEOUS PROPERTY IN SECTION	T. S. R. W.		
4. LOT NO.	, RECORDED PLAT		
5. PRIVATE CLAIMS			

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Keith L. Sackett, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on January 23, 1985, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

- A. Description of original monument and accessories and/or subsequent restoration:
- Corner C5: Found old post and probable original bearing tree sugar 8" N40E 16 links
It is now 24" sugar with old face and chopping.
- Corner C3: Original monument and accessories not found. Found old hemlock stump which fits for original BT. No positive identification.
- Corner C1: Original monument and accessories not found. Found 2" angle iron by Co Rd Co
- B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:
- Corner C5: Restored at old post.
- Corner C3: Restored from old hemlock stump BT. This position fits good with other corners in area.
- Corner C1: Restored at Marquette Co. Rd. Commission angle iron.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- Corner C5: Set 1" I.D. by 32" I.P. with 4" aluminum cap. 7" sugar N58W 6.5' S7, NBT
7" sugar S45E 2.9' S17, NBT
7" sugar S40W 14.3' S18, NBT
Probable original BT → 24" sugar N45E 10.5'
- Corner C3: Set 1" I.D. by 32" I.P. with 4" aluminum cap. 4" sugar N66E 5.2' S5, NBT
7" sugar S05W 16.8' S7, NBT
8" sugar N70W 11.2' S6, NBT
- Corner C1: 2" angle iron 5' high 10" maple N72E 7.0' S31, NBT
8" maple S38W 16.0' S6, NBT
6" maple S70E 20.1' S5, NBT

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Keith L. Sackett DATE 2-2-85

CHIEF OF SURVEY PARTY
MICHIGAN REGISTERED LAND SURVEYOR
Keith L. Sackett
Department of Natural Resources

SURVEYOR'S MICHIGAN REGISTRATION NO. 19006

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1978

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET