

APR 06 1999

SECTION

Approved by Menominee County
 Land Survey Remonumentation
 Peer Group Under Act 345 Of

P.A. 011990 On 12/14 1998
Terence S. Wanic, P.S.
 Chairman

LAND CORNER RECORDATION CERTIFICATE
 Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

MENOMINEE

(County)

Located In:

Corner Code #

1. Public Land Survey

T 33 N R 26 W

G-08

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

4. Lot No. , Recorded Plat

5. Private Claims

I, William Lenca, in a field survey on Mar. 24, 19 98 do hereby state that under
 requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in
 conformance with regulations and rules therefore as required in the current manual of survey instructions of the
 United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or
 that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan
 Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,
 recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
 on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

- 1848: Original Survey by James H. Mullett - B.T.'s - Birch, 14" - S02°W - 24 lks.; Hemlock, 16" - S15°E - 08 lks. All original
 evidence for this corner has been destroyed by logging activities.
 1980: Certified Survey Number 197 by George B. Wilson, RLS 17607, shows this corner as it relates to other corners in Section
 22, T33N-R26W. The corner monument is described as a 4" square concrete monument.
 1987: Certified Survey No. 510 by William Lenca, RLS 26461, shows this corner as it relates to other corners in Section 21,
 T33N-R26W.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We found a 4 inch square concrete monument (as indicated in Certified Survey Number 197) in line with ancient fences North and
 East. This monument falls within 2 feet of being halfway between Section Corners, has been used by local surveyors for at least 18
 years, and is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 3-1/4" dia. Alum cap stamped for corner location on existing concrete monument:

7" dia. Maple	S82°E	6.17 feet	Scr. NBT
9" dia. Cedar	S19°E	24.12 feet	Scr. NBT
6" dia. Maple	N79°W	12.38 feet	Scr. NBT
10" dia. Hemlock	N16°W	29.19 feet	Scr. NBT
Metal Survey Sign Post	North	0.2 feet	

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca
 Surveyor's Michigan License No. 26461

Date Dec. 10, 1998

RECEIVED FOR RECORD
 98 DEC 14 PM 3:22
 PAGE # 687 BKS
 BARBARA MORRISON
 REGISTER OF DEEDS
 MENOMINEE MI 49865

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

