

**LAND CORNER RECORDATION CERTIFICATE**  
**Filing Requirement of Act 74, Mich. P.A. 1970**

For corners in

<u>Menominee</u> <small>(County)</small>	Located In:	Corner Code <u>J-6</u>
1. Public Land Survey	T <u>34N</u> R <u>26W</u>	<u>J-6</u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
	T <u>    </u> R <u>    </u>	<u>    </u>
2. Property Controlling in Section	S <u>14</u> T <u>34N</u> R <u>26W</u>	<u>9, 16</u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
3. Miscellaneous Property in Sec.	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>
	S <u>    </u> T <u>    </u> R <u>    </u>	<u>    </u>

**Register of Deeds Stamp & File Number**

4. Lot No.     , Recorded Plat       
 5. Private Claims

I, David Babbitt, in a field survey on 8/21/86, 19    , do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

J-6. Center 1/4 corner of Section 14.  
 Not prev. est.

9. East 1/16 corner of Section 14 (on the E and W 1/4 line). Not prev. est.

16. East 1/16 corner on South section line of Section 14. Not prev. est.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

J-6. Set at the intersection of the N-S and E-W 1/4 lines of Section 14.

9. Set MPOL between the East 1/4 corner and the center of Section 14.

16. Set MPOL between the S 1/4 corner and the SE section corner of Section 14.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

J-6. D.N.R. Monument.  
 31" h.maple N37E, 91.2'  
 18" h.maple S85W, 57.9'  
 12" h.maple N60W, 80.85'  
 12" twin h.maple N29W, 72.45'

9. D.N.R. Monument  
 8" h.maple S64W, 22.1'  
 6" h.maple N12W, 12.4'  
 4" h.maple N35E, 17.8'  
 10" h.maple S69E, 20.3'

16. D.N.R. Mon. buried in road.  
 8" tamarack S10E, 23.7'  
 3" w.pine S36E, 28.3'  
 5" tamarack N26E, 22.3'  
 6" tamarack N37W, 44.4'

Signed by David B. Babbitt

Date 9-11-86

Surveyor's Michigan License No. 21558