

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee (County)	Located In:	Corner Code #
1. Public Land Survey	T 34N R 29W	MC W of H03[006]
	T R	
	T R	
2. Property Controlling in Section	S T R	
	S T R	
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5			4		3		2		1	
3													
4	7		8			9		10		11		12	
5													
6	18		17			16		15		14		13	
7													
8	19		20			21		22		23		24	
9													
10	30		29			28		27		26		25	
11													
12	31		32			33		34		35		36	
13													

I, Jeremy J. Pipp, in a field survey on 3/21/2012AD do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(MC W of H03, Plat Corner)[006] Meander Corner common to Sections 3 and 10 on left bank of
Menominee River. 1852: Francis Coleman, DS. Set meander post witnessed by: Elm 22 S16W
14 links (9.24'); Elm 14 N41W 43 links (28.38'); 1928: Plat of Menominee Forest Estates
#1, depicts a monumented position for the Section line between Sections 3 & 10.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(MC W of H03)[006] No evidence of original survey. Re-established position (noted at
station 189+21.4) using plat monuments found at Stations 190+58.4, 196+20, 205+10.5,
209+82.6, 213+00.7, & 218+01 according to the the Plat of Menominee Forest Estates #1.
Position is accepted as a careful and faithful REESTABLISHMENT of the position of the
original corner AND Position is accepted as a careful and faithful PERPETUATION of the
Plat Corner. (Note: position previously accepted by PS#37270 to set I03)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(MC W of H03)[006] DNR monument
12" Oak N10E 24.95' (MC,NBT)
5" Sugar S15E 9.88' (MC,NBT)
5" Sugar S51W 24.65' (MC,NBT)
7" Sugar S83W 16.54' (MC,NBT)

All trees are blazed, scribed, painted,
and signed. Measurements are to nail in
side of tree, bearings are magnetic. A
metal rail & sign were set West 1.5 feet.

Signed by Jeremy J. Pipp
Surveyor's Michigan License No. 50447



July 16, 2012

For the Michigan Department of Natural Resources, Forest Resources Division