

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee Located In: Corner Code #
1. Public Land Survey T 34N R 29W MC S of K05[010]
2. Property Controlling in Section S T R
3. Miscellaneous Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M) for Register of Deeds Stamp & File Number.

I, Jeremy J. Pipp, in a field survey on 3/22/2012AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(MC S of K05)[010] Meander Corner common to Sections 13 and 14 on left bank of Menominee River. 1852: Francis Coleman, DS. Set meander post witnessed by: Lynn 12 N50E 44 links (29.04'); B. Ash 10 N52W 25 links (16.50').

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(MC S of K05)[010] No evidence of original survey or subsequent restoration found. Corner position reestablished by extending a line from the Northwest corner of Section 12 through the Northwest corner of Section 13. GLO distance from the Section corner to this position is 28.44 Chains (1877.07 feet); this position falls in the water. Monumented witness position 1827.04 feet South of Section Corner and +/-50 Feet from the Waters Edge. Position is accepted as a careful and faithful WITNESS TO the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(MC S of K05)[010] DNR monument
10" Basswood N03E 27.00' (MC,NBT)
13" Basswood N81E 33.87' (MC,NBT)
13" Ash S54W 30.11' (MC,NBT)
14" Basswood N58W 27.84' (MC,NBT)
All trees are blazed, scribed, painted, and signed. Measurements are to nail in side of tree, bearings are magnetic. A metal rail & sign were set North 1.5 feet.

Signed by [Signature] Date July 16, 2012
Surveyor's Michigan License No. 50447



For the Michigan Department of Natural Resources, Forest Resources Division