LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For comers in

Menominee (County)	_ Located In:	Corner Code #	
1. Public Land Survey	T R R T R R T R R R R R R R R R R R R R		
2. Property Controlling in Section	S 13 T 34N R 29W S T R	POŁGvtLtLne	
3. Miscellaneous Property in Sec.	S T R S T R		Position of Deads Charles 5 5th Au
4. Lot No. , Rec 5. Private Claims	corded Plat		Register of Deeds Stamp & File Number A B C D E F G H I J K L M 2 6 5 5 4 4 3 3 3 3 3 1
I, Jeremy J. Pipp , in a field survey on 3/20/2012AD do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey 5			
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of 6 15 15 14 13 15 16 17 16 17 16 17 16 17 18 19 20 21 22 23 24			
re-established, monumented, recover	9 10 30 29 28 27 26 26		
NOTE: Not more than 2 corner on this certificate.	ers, all in the same town and range,	may be recorded	11 12 31 32 33 34 35 36
A. Description of original monument and accessories and/or subsequent restoration:			

(POL Gov't lot E of 03) Meander Corner on line between Government Lots 1 & 2 of Section 13. Not set in original survey, no evidence of subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(POL Gov't lot E of 03) Calculated Government Lot line as being parallel with the North line of said Section 13 and extending East from the North 1/16th corner between Sections 13 & 14. Point on Line is located on line between Government Lots 1 & 2 of Section 13 and is 35 feet East of the Waters edge on the left bank of the Menominee River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(POL Gov't lot E of 03) DNR monument 26" Red Maple N81E 17.37' (MC,BT) 12" Ash S17E 17.85' (MC,BT) 6" Basswood S87W 15.73' (MC,BT) 11" Basswood N22W 11.47' (MC,BT) All trees are blazed, scribed, and painted. Measurements are to nail in side of tree, bearings are magnetic.

JEREMY J.
PIPP
PROFESSIONAL
SURVEYOR
No.
50447

July 16, 2012

Surveyor's Michigan License No.

Signed by

50447

For the Michigan Department of Natural Resources, Office of Land and Facilities