

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF:-	LOCATED IN:-	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 35 ^N XX R. 25 ^{XX} W	F - 12
2. PROPERTY CONTROLLING IN SECTION <u>33</u>	T. 35 ^N XX R. 25 ^{XX} W	9 - 12 - 13
3. MISCELLANEOUS PROPERTY IN SECTION	T. ^N XX S. R. ^E XX W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

**MENOMINEE
CO**

REGISTER OF DEEDS STAMP AND
FILING NUMBER

I, David B. Babbitt do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970 the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were in a field survey on June 24 1975, established, re-established, monumented, re-monumented, recovered, restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

None

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- F - 12 - Set at intersection of N - S and E - W $\frac{1}{4}$ lines.
- 9 - Set M.P.O.L. between ctr. of Sec. and E $\frac{1}{4}$ cor.
- 12 - Set M.P.O.L. between ctr. of sec. and S $\frac{1}{4}$ cor.
- 13 - Set at ctr. of SE $\frac{1}{4}$ sec. by closed traverse around the NE $\frac{1}{4}$ of the SE $\frac{1}{4}$.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

All 1" iron pipe with 4" aluminum cap - all bearings magnetic.

F-12
16" W. birch - S53° E - 7.0'
6" W. birch - S23° W - 17.3'

12
(Square D) 4" Bl. ash - S36° W - 2.7'
4" W. Birch - N12° E - 20.8'

9
5" H. Maple - N31° E - 16.8'
10" W. Birch - S35° W - 11.3'

13
8" H. Maple - N40° E - 24.3'
6" Beech - S50° E - 6.8'

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY

CHIEF OF SURVEY PARTY

MICHIGAN REGISTERED LAND SURVEYOR

DATE 6/25/75

(SEAL)