

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Menominee
 (County)

Located In:

Corner Code 11

- | | | | | | |
|------------------------------------|---|-----|---|-----|-----------|
| 1. Public Land Survey | T | 35N | R | 25W | I-9, H-9. |
| | T | | R | | |
| | T | | R | | |
| | T | | R | | |
| 2. Property Controlling in Section | S | | T | R | |
| | S | | T | R | |
| 3. Miscellaneous | S | | T | R | |
| Property in Sec. | S | | T | R | |

Register of Deeds Stamp & File Number

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, David B. Babbitt in a field survey on 6/15/87, 19____, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

I-9. NE section corner, Section 27 from old map of JW Wells State Park boundary old mon. (a wood stake) replaced by standard mon. 10" cedar, dead S40W, 44.2'
 4" ash, N40E, 23.8'

H-9. North 1/4 corner of Section 27. Wood post. Cedar 10 - N39E, 14 Lks.
 DO 12 - S62E, 10 Lks.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

I-9. Found brass capped conc. mon. on east side of powerline. Re-witnessed as found.

H-9. Set monument at very old fence corner. No other evidence available. Fits recorded distance to NE corner of Section 27 well.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

I-9. Conc. Mon. w/Brass Cap
 9" w.ash N84E, 34.5'
 10" maple S89W, 72.6'
 7" cedar S19W, 32.2'
 5" cedar S29E, 29.6'

H-9. DNR Monument
 8" cedar fence post N15E, 1.0'
 8" cedar fence post S60E, 1.7'
 4" balsam S20W, 2.3'
 Iron fence post S1E, 18.4'

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Signed by

David B. Babbitt

Date

12-3-87

Surveyor's Michigan License No.

21558