

SURVEY &  
RECORDATION

APR 06 1999

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

Approved by Menominee County  
Land Survey Remuneration  
Peer Group Under Act 345 Of

P.A. Of 1990 On 12/30 1998

Chairman

For corners in

MENOMINEE

(County)

Located In:

Corner Code #

1. Public Land Survey

T35NR 28W

J-09

2. Property Controlling  
in Section

S

T

R

T

R

T

R

S

T

R

3. Miscellaneous  
Property in Sec.

S

T

R

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, William Lenca, in a field survey on Oct. 06, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

1852: Original Survey by Francis Coleman - B.T.'s - W. Pine, 10" - N19°E - 12 lks.; W. Pine, 20" - S45°W - 41 lks. All original evidence for this corner has been destroyed by county road improvements.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

We set this corner in the centerline of an East - West county road and in line with ancient fences North - South. This location fits well with measurements to corners 1/2 mile East and 1/2 mile West, and with existing lines of occupation and is accepted as the best available evidence of the position of the original corner.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 5/8" x 24" Iron Rod/3-1/4" dia. Alum. cap stamped for corner location in Monument Box:

10" dia. Tamarack  
16" dia. Maple  
12" dia. Norway Pine  
8" dia. White Pine  
Metal Survey Sign Post

N50°E 43.30 feet  
S23°E 93.21 feet  
S41°W 83.27 feet  
N19°W 66.86 feet  
North 32.2 feet

"X" cut in upper and lower blazes  
"X" cut in upper and lower blazes  
"X" cut in upper and lower blazes  
"X" cut in upper and lower blazes

NOTE: All bearings are magnetic bearings. All distances are measured with steel tape. Distances to trees are to nail in side of tree.

Signed by William Lenca  
Surveyor's Michigan License No. 26461

Date Dec. 18, 1998

