

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Menominee (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
2. Property Controlling in Section	S 28 T 36N R 25W	POL E of 02
	S 28 T 36N R 25W	POL E of 16
	S T R	
3. Miscellaneous Property in Sec.	S T R	
	S T R	
4. Lot No. _____, Recorded Plat		
5. Private Claims		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Jeremy J. Pipp, in a field survey on 1/09/2012AD do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(POL) Point on the North Line of Section 28. Not set in original survey, no evidence of
subsequent establishment.

(POL) Point on the South Line of Section 28. Not set in original survey, no evidence of
subsequent establishment.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(POL) Point on the North Line of Section 28; 14.5 feet West of the Top of Bank of the
Cedar River.

(POL) Point on the South Line of Section 28; 12 feet West of the Top of Bank of the Cedar
River.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(POL) 1" Pipe with Plastic Cap
5" Maple S18W 14.98' (POL,BT)
15" Maple S61W 14.09' (POL,BT)
All trees are blazed, scribed, and
painted. Measurements are to nail in
side of tree, bearings are magnetic.

(POL) 1" Pipe with Plastic Cap
10" Cedar S29W 7.73' (POL,BT)
12" Cedar N41W 17.23' (POL,BT)
All trees are blazed, scribed, and
painted. Measurements are to nail in
side of tree, bearings are magnetic.

Signed by Jeremy J. Pipp
Surveyor's Michigan License No. 50447



Date July 16, 2012

For the Michigan Department of Natural Resources, Office of Land and Facilities

20013

20015